



LED INTERIOR FIXTURES

Superior Life® LED Interior Fixtures are high quality with integrated LEDs for efficiency and optimal performance. They consume up to less energy than a traditional lighting, significantly reducing operating costs and are environmentally friendly.

- **CONSTRUCTION**
Die form cold-rolled steel housing
- **DIMMING**
0-10V dimming function, dimming range is 10% - 100%
- **LONG LIFE**
Up to 150,000 projected life for reduced maintenance.
- **MOUNTING**
Compatible with today's popular ceiling system.

Dimmable LED By incorporating advanced circuitry into our LED products, SUPERIOR LIFE® dimmable LED fixture function with switch dimmers by allowing full linear dimming control.



ITEM#	DESCRIPTION	WATTS	CCT	LM	LM/W	BEAM	CRI	VOLTS	LIFE	CASE
55236	LED 48" DESIGNER STRIP - 18W/40K/120-277V/DIMMABLE - SL® DLC	18	40K	2340	130	130°	80	120-277	50K	6
55245	LED 48" DESIGNER STRIP - 18W/50K/120-277V/DIMMABLE - SL® DLC	18	50K	2358	131	130°	80	120-277	50K	6
55238	LED 48" DESIGNER STRIP - 32W/40K/120-277V/DIMMABLE - SL® DLC	32	40K	4224	132	130°	80	120-277	50K	6
55248	LED 48" DESIGNER STRIP - 32W/50K/120-277V/DIMMABLE - SL® DLC	32	50K	4256	133	130°	80	120-277	50K	6
55241	LED 96" DESIGNER STRIP - 38W/40K/120-277V/DIMMABLE - SL® DLC	38	40K	4940	130	130°	80	120-277	50K	6
55249	LED 96" DESIGNER STRIP - 38W/50K/120-277V/DIMMABLE - SL® DLC	38	50K	4978	131	130°	80	120-277	50K	6
55243	LED 96" DESIGNER STRIP - 65W/40K/120-277V/DIMMABLE - SL® DLC	65	40K	8580	132	130°	80	120-277	50K	6
55244	LED 96" DESIGNER STRIP - 65W/50K/120-277V/DIMMABLE - SL® DLC	65	50K	8645	133	130°	80	120-277	50K	6
55270	LED 2 X 2 TROFFER - 34W/40K/120-277V/DIMMABLE - SL® DLC	34	40K	3400	100	100°	80	120-277	50K	1
55272	LED 2 X 4 TROFFER - 42W/40K/120-277V/DIMMABLE - SL® DLC	42	40K	4536	108	100°	80	120-277	50K	1
55266	LED 2 X 2 DIRECT/INDIRECT - 30W/40K/120-277V/DIMMABLE - SL® DLC	30	40K	3780	126	120°	80	120-277	50K	1
55265	LED 2 X 2 DIRECT/INDIRECT - 30W/50K/120-277V/DIMMABLE - SL® DLC	30	50K	3810	127	120°	80	120-277	50K	1
55268	LED 2 X 4 DIRECT/INDIRECT - 34W/40K/120-277V/DIMMABLE - SL® DLC	34	40K	4284	128	120°	80	120-277	50K	1
55267	LED 2 X 4 DIRECT/INDIRECT - 34W/50K/120-277V/DIMMABLE - SL® DLC	34	50K	4318	127	120°	80	120-277	50K	1
55259	LED WRAP A-ROUND 8"x 48" 42W/40K/FR/120-277V/DIMMABLE - SL® DLC	42	40K	4410	105	100°	80	120-277	50K	4
55260	LED WRAP A-ROUND 8"x 48" 42W/50K/FR/120-277V/DIMMABLE - SL® DLC	42	50K	4452	106	100°	80	120-277	50K	4
55171	LED 2 X 2 TROFFER RETROFIT/CENTER BASKET/34W/40K/120-277V/DIMMABLE - SL® DLC	34	40K	4216	125	100°	80	120-277	50K	1
55254	LED VAPOR TIGHT 48" 40W/40K/FROSTED LENS/120-277V/DIMMABLE - SL® DLC	40	40K	4400	110	120°	80	120-277	50K	4
55251	LED VAPOR TIGHT 48" 40W/50K/FROSTED LENS/120-277V/DIMMABLE - SL® DLC	40	50K	4480	112	120°	80	120-277	50K	4
55256	LED VAPOR TIGHT 48" 65W/40K/FROSTED LENS/120-277V/DIMMABLE - SL® DLC	65	40K	7150	110	120°	80	120-277	50K	4
55253	LED VAPOR TIGHT 48" 65W/50K/FROSTED LENS/120-277V/DIMMABLE - SL® DLC	65	50K	7540	116	120°	80	120-277	50K	4

Key: SL = Superior Life® / LM = Lumens

NOTE: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly.



PREMIUM QUALITY LIGHTING® • www.PQLighting.com

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, Ca 93065 • 800.323.8107 • Fax: 877.619.7053

GO GREEN

