



# LED PAR LAMPS

REFLECTOR • NARROW FLOOD

Superior Life® PAR lamps are an efficient way to light sockets once reserved for traditional lamps. They consume up to 86% less energy, thereby significantly reducing operating costs. The superior life hours of these lamps make them ideal for hard to reach places, reducing maintenance.

## FEATURES

- Superior lighting performance.
- Energy efficient.
- Lightweight and easy installation.
- Compact design and focused lighting.
- Resembles traditional lighting.
- Mercury Free - Environmentally friendly.
- Low heat reduces AC costs.

## Dimmable

Superior Life® dimmable LED lamps function with wall dimmers just as normal incandescents do by allowing full linear dimming control. *(When applicable)*

## APPLICATIONS

### RESIDENTIAL & COMMERCIAL



General Lighting  
Recessed Cans  
Track Lighting  
Ceiling Fixtures

## WARRANTY



## QUALIFICATIONS



Qualifications vary, see technical data for specific information.



PREMIUM QUALITY LIGHTING® • [www.PQLighting.com](http://www.PQLighting.com)  
© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065 • 800-323-8107 • Fax: 877-619-7053

GO GREEN  
04/2019

# LED PAR LAMPS



## PAR20 LAMPS

LED INDOOR LAMPS - LED PAR20

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
<b>DIMMABLE</b>														
7	91362	7PAR20/30K/25°/DIMMABLE/V5 - SL®		3000K	520	74	25°	80	3.4"	120	MEDIUM	10K	50W	48
8	90937	8PAR20/30K/25°/DIMMABLE/V4 - SL®		3000K	500	63	25°	83	3.4"	120	MEDIUM	25K	50W	20
	91734	8PAR20/27K/25°/DIMMABLE/V6 - SL®	★	2700K	488	61	25°	91	3.4"	120	MEDIUM	15K	50W	48
	91735	8PAR20/30K/25°/DIMMABLE/V6 - SL®	★	3000K	500	63	25°	91	3.4"	120	MEDIUM	15K	50W	48
	91736	8PAR20/40K/25°/DIMMABLE/V6 - SL®	★	4000K	500	63	25°	94	3.4"	120	MEDIUM	15K	50W	48
8.5	91366	8.5PAR20/50K/25°/DIMMABLE/V5 - SL®	★	5000K	520	61	25°	94	3.4"	120	MEDIUM	25K	50W	48

## PAR30 SN LAMPS

LED INDOOR LAMPS - LED PAR30/SN

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
<b>DIMMABLE</b>														
12	91741	12PAR30/50K/DIMMABLE/V6 - SL®	★	5000K	800	67	25°	87	3.3"	120	MEDIUM	15K	75W	24
13	91367	13PAR30/27K/DIMMABLE/V5 - SL®	★	2700K	800	62	25°	92	3.5"	120	MEDIUM	25K	75W	24
	91368	13PAR30/30K/DIMMABLE/V5 - SL®	★	3000K	800	62	25°	92	3.5"	120	MEDIUM	25K	75W	24
	91369	13PAR30/40K/DIMMABLE/V5 - SL®	★	4000K	800	62	25°	92	3.5"	120	MEDIUM	25K	75W	24
	91370	13PAR30/50K/DIMMABLE/V5 - SL®	★	5000K	800	62	25°	95	3.5"	120	MEDIUM	25K	75W	24

## PAR30 LN LAMPS

LED INDOOR LAMPS - LED PAR30/LN

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
<b>DIMMABLE</b>														
11	91392	11PAR30/27K/BLACK/DIMMABLE/V5 - SL®	★	2700K	800	62	40°	91	4.6"	120	MEDIUM	25K	75W	24
12	91745	12PAR30/27K/DIMMABLE/V6 - SL®	★	2700K	800	67	25°	92	4.3"	120	MEDIUM	15K	75W	24
	91746	12PAR30/30K/DIMMABLE/V6 - SL®	★	3000K	800	67	25°	95	4.3"	120	MEDIUM	15K	75W	24
	91747	12PAR30/40K/DIMMABLE/V6 - SL®	★	4000K	800	67	25°	95	4.3"	120	MEDIUM	15K	75W	24
	91748	12PAR30/50K/DIMMABLE/V6 - SL®	★	5000K	800	67	25°	96	4.3"	120	MEDIUM	15K	75W	24
	13	91374	13PAR30/50K/DIMMABLE/V5 - SL®	★	5000K	800	63	25°	95	4.6"	120	MEDIUM	25K	75W
<b>NON-DIMMABLE</b>														
25	91480	25PAR30/40K/V6 - SL®		4000K	2500	100	25°	80	4.7"	120-277	MEDIUM	25K	75W	12

## PAR38 LAMPS

LED INDOOR LAMPS - LED PAR38

WATTS	ITEM#	DESCRIPTION	ENERGY STAR®	CCT	LUMENS	LM/W	BEAM	CRI	MOL	VOLTS	BASE	LIFE	TRAD. EQUIV.	CASE
<b>DIMMABLE</b>														
17	91752	17PAR38/27K/25°/DIMMABLE/V6 - SL®	★	2700K	1200	73	25°	93	4.8"	120	MEDIUM	15K	120W	24
	91767	17PAR38/30K/40°/DIMMABLE/V6 - SL®	★	3000K	1200	73	40°	95	4.8"	120	MEDIUM	15K	120W	24
	91754	17PAR38/40K/25°/DIMMABLE/V6 - SL®	★	4000K	1200	73	25°	95	4.8"	120	MEDIUM	15K	120W	24
	91755	17PAR38/50K/25°/DIMMABLE/V6 - SL®	★	5000K	1200	73	25°	96	4.8"	120	MEDIUM	15K	120W	24
19	91381	19PAR38/30K/25°/DIMMABLE/V5 - SL®	★	3000K	1200	63	25°	92	5.1"	120	MEDIUM	25K	120W	24
	91385	19PAR38/30K/40°/DIMMABLE/V5 - SL®	★	3000K	1200	63	40°	92	5.1"	120	MEDIUM	25K	120W	24
<b>NON-DIMMABLE</b>														
13	91379	13PAR38/30K/40°/V5 - SL®		3000K	1000	77	40°	80	5.1"	120	MEDIUM	25K	120W	24
15	90775	15PAR38/FL/50K/38°/AC 100-277V - SL®		5000K	1500	100	38°	80	5.0"	100-277	MEDIUM	50K	120W	50
17	91758	17PAR38/30K/25°/V6 - SL®		3000K	1200	71	25°	90	4.8"	120-277	MEDIUM	40K	120W	24

Key: SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are Energy Star qualified. Visit [www.energystar.gov](http://www.energystar.gov) to confirm qualification • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.



PREMIUM QUALITY LIGHTING® • [www.PQLighting.com](http://www.PQLighting.com)  
 © P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065 • 800-323-8107 • Fax: 877-619-7053

GO GREEN  
04/2019

