



LED STADIUM LIGHTING

OUTDOOR AREA LIGHTING • HIGH LUMEN OUTPUT

Superior Life® LED Stadium lights are energy efficient high performance luminaries designed to replace existing HID sports light fixtures. Advanced optics provide bright uniform light with a long life (50,000 hrs), significantly reducing maintenance costs and energy use over the life of the fixture. The construction allows excellent heat dispersion, convenient installation and is weather resistant.

FEATURES

- High Efficiency, Energy Saving
- High Lumen Per Watt Design - Bright uniform light distribution.
- Modern and durable design with improved heat dispersion
- Adjustable light angle, up to 240°
- Surge protection built-in for added protection

APPLICATIONS

COMMERCIAL & INDUSTRIAL



- | | |
|------------|--------------|
| Arenas | Courtyards |
| Gymnasiums | Public Areas |
| Stadiums | Airports |

WARRANTY



QUALIFICATIONS



Qualifications vary, see technical data for specific information.





STADIUM LIGHTING

LED STADIUM LIGHT

WATTS	SKU#	DESCRIPTION	QUALIFICATION MODEL#	DLC*	CCT	LUMENS	LM/W	BEAM	CRI	VOLTS	TRAD. EQUIV.	CASE
100-277V - NON-DIMMABLE												
302	84100	300W STADIUM/50K/30°/100-277V/TRUNNION - SL°	L-STDm-300-MV-1-50K	★	5000K	40032	132	30°	83	100-277	1000W	1
404	84101	400W STADIUM/50K/30°/100-277V/TRUNNION - SL°	L-STDm-400-MV-1-50K	★	5000K	51464	127	30°	83	100-277	1500W	1
504	84102	500W STADIUM/50K/30°/100-277V/TRUNNION - SL°	L-STDm-500-MV-1-50K	★	5000K	66070	131	30°	83	100-277	1500W+	1
605	84103	600W STADIUM/50K/40°/100-277V/TRUNNION - SL°	L-STDm-600-MV-1-50K	★	5000K	79538	131	40°	74	100-277	1500W+	1
750	84104	750W STADIUM/50K/40°/100-277V/TRUNNION - SL°	L-STDm-750-MV-1-50K	★	5000K	98590	132	40°	73	100-277	1500W+	1
1259	84106	1250W STADIUM/50K/40°/100-277V/TRUNNION - SL°	L-STDm-1250-MV-DH-1-50K	★	5000K	165590	132	40°	72	100-277	1500W+	1
200-480V - NON-DIMMABLE												
307	84107	300W STADIUM/50K/30°/200-480V/TRUNNION - SL°	L-STDm-300-480-1-50K	★	5000K	40617	133	30°	84	200-480	1000W	1
404	84108	400W STADIUM/50K/30°/200-480V/TRUNNION - SL°	L-STDm-400-480-1-50K	★	5000K	51484	127	30°	83	200-480	1500W	1
502	84109	500W STADIUM/50K/30°/200-480V/TRUNNION - SL°	L-STDm-500-480-1-50K	★	5000K	66004	132	30°	83	200-480	1500W+	1
604	84110	600W STADIUM/50K/40°/200-480V/TRUNNION - SL°	L-STDm-600-480-1-50K	★	5000K	79422	132	40°	74	200-480	1500W+	1
748	84111	750W STADIUM/50K/40°/200-480V/TRUNNION - SL°	L-STDm-750-480-1-50K	★	5000K	98120	131	40°	73	200-480	1500W+	1
1256	84113	1250W STADIUM/50K/40°/200-480V/TRUNNION - SL°	L-STDm-1250-480-DH-1-50K	★	5000K	165154	132	40°	72	200-480	1500W+	1

Some items may be special order; please consult with P.Q.L.

Key: SL = Superior Life® / LM = Lumens / TRAD. EQUIV. = Traditional Equivalent

Note: Not all product variations listed on this page are DLC qualified. Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice. • Photos and drawings may not be to scale and are for general reference only.

