



## T8 Ballasts - Reduced Wattage



**PREMIUM QUALITY LIGHTING**  
800.323.8107 • 805.579.8279  
www.pqlighting.com

- UL Listed
- Sound Rating - Class A
- Min. Starting Temperature - 0 F
- Meets FCC Part 18C, Class A
- Outdoor Type 1
- No PCB's
- Crest Factor - Less than 1.70
- Power Factor (P.F) -> 0.98
- Input Frequency - 60 Hz



### Electronic Ballast Specifications

CODE #	BALLAST MODELS	LAMPS			VOLTAGE	POWER	INPUT WATTS	BEF	BALLAST FACTOR	DIMENSIONS			
		TYPE	QTY							L	W	H	MTG CENTER
70201	1/32IS-120/277	F32 T8	1		120/277	28W	24	3.62	0.87nom	9.50"	1.65"	1.18"	8.91"
70209	1/32IS-120	F32 T8	1		120	28W	25	3.52	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	1/32IS-270	F32 T8	1		277	28W	25	3.52	0.88nom	9.50"	1.65"	1.18"	8.91"
70201	2/32IS-120/277	F32 T8	2		120/277	28W	47/46	1.85/1.89	0.87nom	9.50"	1.65"	1.18"	8.91"
70209	2/32IS-120	F32 T8	2		120	28W	50	1.76	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	2/32IS-277	F32 T8	2		277	28W	50	1.76	0.88nom	9.50"	1.65"	1.18"	8.91"
70204	3/32IS-120/277	F32 T8	3		120/277	28W	71/69	1.22/1.26	0.87nom	9.50"	1.65"	1.18"	8.91"
70212	3/32IS/120	F32 T8	3		120	28W	75	1.17	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	3/32IS/277	F32 T8	3		277	28W	75	1.17	0.88nom	9.50"	1.65"	1.18"	8.91"
70204	4/32IS-120/277	F32 T8	4		120/277	28W	96	0.91	0.87nom	9.50"	1.65"	1.18"	8.91"
70212	4/32IS-120	F32 T8	4		120	28W	100	0.88	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	4/32IS-277	F32 T8	4		277	28W	100	0.88	0.88nom	9.50"	1.65"	1.18"	8.91"
70201	1/32IS-120/277	F32 T8	1		120/277	25W	22	3.95	0.87nom	9.50"	1.65"	1.18"	8.91"
70209	1/32IS-120	F32 T8	1		120	25W	22	4	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	1/32IS-270	F32 T8	1		277	25W	22	4	0.88nom	9.50"	1.65"	1.18"	8.91"
70201	2/32IS-120/277	F32 T8	2		120/277	25W	44/43	1.98/2.02	0.87nom	9.50"	1.65"	1.18"	8.91"
70209	2/32IS-120	F32 T8	2		120	25W	44	2	0.88nom	9.50"	1.65"	1.18"	8.91"
70200	2/32IS-277	F32 T8	2		277	25W	44	2	0.88nom	9.50"	1.65"	1.18"	8.91"
70204	3/32IS-120/277	F32 T8	3		120/277	25W	66/65	1.32/1.34	0.87nom	9.50"	1.65"	1.18"	8.91"
70212	3/32IS/120	F32 T8	3		120	25W	66	1.33	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	3/32IS/277	F32 T8	3		277	25W	66	1.33	0.88nom	9.50"	1.65"	1.18"	8.91"
70204	4/32IS-120/277	F32 T8	4		120/277	25W	88	0.99	0.87nom	9.50"	1.65"	1.18"	8.91"
70212	4/32IS-120	F32 T8	4		120	25W	88	1	0.88nom	9.50"	1.65"	1.18"	8.91"
70203	4/32IS-277	F32 T8	4		277	25W	88	1	0.88nom	9.50"	1.65"	1.18"	8.91"