



Item#: 54871
BI-LEVEL PIR MOTION &
DAYLIGHT SENSOR
ISO FIXTURE ACCESSORY

FEATURES

- Provides multi-level control based on motion and/or daylight contribution.
- Controls 0-10V VDC LED drivers or dimming ballasts
- 360° detection range.
- Adjustable light levels and stand-by time.
- All control parameters are adjustable by using the RC-100 remote (sold separately)


APPLICATION


Sensor is designed for use with select PQL fixtures with 12-24VDC AUX installed sensor socket.

PREMIUM QUALITY LIGHTING®

ELECTRICAL	
Power Supply	12-24VDC, >30mA
PERFORMANCE	
Dim Control Ouput	0-10V / Max. 25mA Sinking Current
Detection Sensitivity	20% / 50% / 75% / 100%
Detection Diameter	At max. height 60ft
Mounting Height	Max. 40ft
Time Settings	10s / 1min / 5min / 10min / 20min / 30min / 60min
Lighting Control	24H / 10 Lux / 30 Lux / 50 Lux
ENVIRONMENT	
Operating Temperature	-4° ~ 140°F
Suitable Location	WET
Ingress Protection Rating	IP65
LIFESPAN	
Warranty (Years)	
CONSTRUCTION	
Housing	PC
Mounting	Screw In
Finish	White

SENSOR COVERAGE





Specifications are subject to change without notice.

Item#: **54871 BI-LEVEL PIR MOTION & DAYLIGHT SENSOR**





DIMENSIONS (Inches)

Width/Diameter (MOD)	2.2"
Height	2.2"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW





PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	100	10811768025979	12.6" x 12.6" x 10.4"	
Individual Box	1	811768025972	2.4" x 2.4" x 2.4"	
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
54871	BI-LEVEL PIR MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT	100
ACCESS	ORIES	
54876	ORIES EXTERNAL SWIVEL QUICK CONNECT ADJUSTABLE ELBOW	100

ADDITIONAL INFORMATION:

Factory Default Settings: Sensitivity set to 100%. Hold on time 5 minutes. Daylight sensor is disabled (Set at 🜣). Dimming level at 30%. Dimming time at 60 minutes.