



Item#: 54872 **BI-LEVEL MICROWAVE MOTION & DAYLIGHT SENSOR**

ISO FIXTURE ACCESSORY

FEATURES

- · Provides multi-level control based on motion and/or daylight contribution.
- · Slim, low-profile.
- 360° detection range.
- Adjustable light levels and stand-by time.
- · All control parameters are adjustable by using the RC-100 remote (sold separately)


APPLICATION


Sensor is designed for use with select PQL fixtures with 12-24VDC AUX installed sensor socket.

ELECTRICAL

12-24VDC, >50mA
5.8GHz ± 75MHz
<0.2mW
0-10V / Max. 25mA Sinking Current
20% / 50% / 75% / 100%
Up to 52ft
Max. 40ft
10s / 1min / 5min / 10min / 20min / 30min / 60min
24H / 10 Lux / 30 Lux / 50 Lux
-40° ~ 158°F
WET
IP65
PC
Screw In
White
out notice.

SENSOR COVERAGE





Width of Coverage up to 52ft


Item#: **54872 BI-LEVEL MICROWAVE MOTION & DAYLIGHT SENSOR**




DIMENSIONS (Inches)

Width/Diameter (MOD)	2.2″
Height	1.6″
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		





PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	100	10811768020714	10.6" x 10.6" x 8.9"	
Individual Box	1	811768020717	2" x 2" x 2"	
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
54872	BI-LEVEL MICROWAVE MOTION & DAYLIGHT SCREW-IN SENSOR FOR ISO STRIPS & VAPOR TIGHTS/40FT	100
ACCESS	ORIES	
ACCESS 54876	ORIES External Swivel Quick Connect Adjustable Elbow	100

ADDITIONAL INFORMATION:

Factory Default Settings: Sensitivity set to 100%. Hold on time 5 minutes. Daylight sensor is disabled (Set at 🌣). Dimming level at 30%. Dimming time at 60 minutes.