





Item#: 55043
LED 48" NARROW STRIP FIXTURE
LED READY FIXTURE

FEATURES

- Use 30% less energy than a traditional fluorescent fixture
- · Die formed, and rigidly fabricated
- LED ready with non-shunted sockets
- · Pre-wired at one end
- · Designed for surface or chain mounting

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Lamp Type (not included)	Т8
Number of Lamps	1
Voltage	120-277V

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Warranty (Years) 2

CONSTRUCTION

Housing	22 Gauge C.R.S	
Reflector	86% MIRO4 Aluminum	
Base / Power Supply	Hard Wired	
Finish	High Gloss Baked White Enamel	

QUALIFICATIONS



Operating temperature may vary depending on the lamps used. • Specifications are subject to change without notice.

Item#: **55043 LED 48" NARROW STRIP FIXTURE**






DIMENSIONS (Inches)

Length	48"
Width	2.9"
Height	2.1"
Weight (Lbs)	







PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768025880	49.2" x 3.3" x 2.3"	4.4
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55043	LED 48" NARROW STRIP FIXTURE FOR 1/T8 - SUPERIOR LIFE°	1
ACCESSORIES		
54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W • 120/277V - SUPERIOR LIFE®	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898 - SUPERIOR LIFE®	100

ADDITIONAL INFORMATION:

• Pairs with Superior Life® Direct Wire Single-End or Double-End UL Type B Lamps. Single-end pre-wired fixtures can also be wired double-end by the end-user if needed. Follow specific lamp installation wiring instructions for correct wiring.