



Item#: 55091 LED 2X2 CENTER BASKET

2X2 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

- · Indirect lighting reduces shadows and glare.
- Center basket provides soft ambient light.
- Compatible with today's popular ceiling system.
- Use 30% less energy than a linear fluorescent fixture.
- Smooth edges for easy handling.
- Diffusing lens gives soft even lights.

MOUNTING

- · Recessed ceiling mount.
- Exposed T-grid ceiling.

APPLICATION

Ideal for offices, retail, commercial buildings and work areas.

ELECTRICAL

Wattage	30W
Voltage	120-277V
Current	0.25A
Power Factor	0.9
Total Harmonic Distortion (THD)	10
LIGHTING PERFORMANCE	
Lumens	3780
Lumens Per Watt (LPW)	126
Color Temperature (CCT)	4000K
Color Rendering (CRI)	82
R9 (Red Value)	7
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B2 - U1 - G1
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%
ENVIRONMENT	
Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40
LIFESPAN	
Average Life (Hours)	50,000
Warranty (Years)	5
COMPONENTS	
LED Light Source	Seoul 3528
Driver	SIF30-10650
CONSTRUCTION	
Housing	24 Gauge Steel

QUALIFICATIONS

Base / Power Supply



Lens

Finish



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.

Acrylic (PMMA)

Hard Wired

White


Item#: **55091**LED 2X2 CENTER BASKET



-	184		101	^					
•	IIVI	-	u ∿ ı	.,	NS	1	lnc	hac	۱

Length	23.8"
Width	23.8"
Height	2.1"
Net Weight (Lbs)	6.8

Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768028918	24.2" x 24" x 4.8"	
Item	1	811768028911	N/A	N/A
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55091	LED 2X2 CENTER BASKET/30W/40K/DIMM/120-277V - DLC°	2
REPLACEMEN'	T PARTS	
SIF30-I0650	REPLACEMENT DRIVER	1