



# Item#: **55094**LED 2X2 SPEC-SELECT™ CENTER BASKET TROFFER

2X2 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

# **FEATURES**

Spec-Select™ Troffers feature adjustable wattage and color temperature for the perfect balance of light in any application.

- Energy efficient
- No flickering

#### **APPLICATION**

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other residential and commercial applications.

#### **ELECTRICAL**

Wattage	30W / 35W / 40W
Voltage	120-277V
Current	0.33-0.14A
Power Factor	0.9
Total Harmonic Distortion (THD)	14.1

#### **LIGHTING PERFORMANCE**

Lumens	3780 / 4410 / 5040
Lumens Per Watt (LPW)	126
Color Temperature (CCT)	3500K / 4100K / 5000K
Color Rendering (CRI)	83
R9 (Red Value)	7
R13 (Skin Tones)	
Beam Angle	100°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B2 - U2 - G1
Dimmable Lighting Control	<b>("Dimmable</b> 0-10V, Range 10% - 100%

#### **ENVIRONMENT**

Operating Temperature	-4 ~ 122°F		
Suitable Location	DAMP		
Ingress Protection Rating	IP40		

#### **LIFESPAN**

Warranty (Years)	5
Average Life (Hours)	50,000

#### **COMPONENTS**

LED Light Source	Seoul 3528
Driver	SIF40-10850

### **CONSTRUCTION**

Housing	Aluminum		
Lens	Acrylic (PMMA)		
Base / Power Supply	Hard Wired		
Finish	White		

# **QUALIFICATIONS**





Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


# Item#: **55094**LED 2X2 SPEC-SELECT™ CENTER BASKET TROFFER



				hes)

Length	23.8"
Width	23.8"
Height	2.1"
Net Weight (Lbs)	6.8

<b>SUPPORTING DOCUMENTS</b> (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	<b>GROSS WEIGHT</b> (Lbs)
Master Carton	2	10811768020745	24.5" x 24.4" x 3.3"	10.6
Item	1	811768020748	N/A	N/A
Country of Origin	China			
HS Tariff	9405.10.6020			

#### **ORDERING**

ITEM#	DESCRIPTION	CASE
55094	LED 2X2 SPEC-SELECT™ CENTER BASKET TROFFER/30-35-40W/35-50K/DIMM/120-277V - <b>DLC</b> °	2
REPLACEMEN	IT PARTS	
SIF40-I0850	REPLACEMENT LED DRIVER	1

## **ADDITIONAL INFORMATION:**

- Default settings; 40W, 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. The color temperature and wattage should be selected prior to installation.

