



Item#: 55119-8WEM LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER

2X2 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

Spec-Select™ Center Basket Troffers are like 9 fixtures in 1, featuring adjustable wattage and color temperature for the perfect balance of light in any application.

- Adjustable Wattage (3 settings)
- Adjustable Color (3 settings)
- Integrated Sensor Option (ISO). Sensor sold separately.
- 8W emergency battery pre-installed.
- Designed for T-grid ceilings.

APPLICATION

Offices, hospitals, retail stores, schools lobbies and commercial buildings and work areas.

ELECTRICAL

Wattage	34W / 42W / 50W
Voltage	120-277V
Current	50W @ 120V = 0.42A
Power Factor	0.9
Total Harmonic Distortion (THD)	10.4

LIGHTING PERFORMANCE

Lumens	4250 / 5250 / 6250	
Lumens Per Watt (LPW)	125	
Color Temperature (CCT)	3500K / 4100K / 5000K	
Color Rendering (CRI)	82	
R9 (Red Value)	5	
Beam Angle	100°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U2 - G1	
Dimmable Lighting Control	From optional 12VDC sensor, or customer 0-10V controls.	

ENVIRONMENT

Operating lemperature	-4 ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Seoul 3528
Driver	SIF50-I1100-SS
Emergency Battery	
Sensor Socket	12VDC AUX.

CONSTRUCTION

Housing	Aluminum
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


Item#: **55119-8WEM**LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER



DIMENSIONS (Inches)

Length	47.8"
Width	23.7"
Height	2.1"
Net Weight (Lbs)	

Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	2	10811768026730	48.4" x 24.4" x 4.9"	
Item	1	811768026733	N/A	N/A
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55119-8WEM	LED 2X4 SPEC-SELECT™ CENTER BASKET TROFFER/34-42-50W/35-50K/DIMM/ISO/120-277V/8W EMB - DLC °	2
ACCESSORIES		
54895	PIR DAYLIGHT HARVESTING MICROWAVE SENSOR FOR ISO TROFFER/10-14DC	200
REPLACEMENT	PARTS	
	EM BATTERY	1
SIF50-I1100-SS	REPLACEMENT LED DRIVER	1

ADDITIONAL INFORMATION:

- Default settings; 34W, 5000K.
- When the fixture is in emergency mode the color temperature will default to 5000K.
- The color temperature and wattage may be adjusted by two slide switches integrated into the driver. For additional information refer to the install instructions.

