



Item#: 55272 LED 2X4 RECESSED TROFFER

2X4 LUMINARIES FOR AMBIENT LIGHTING OF INTERIOR COMMERCIAL SPACES

FEATURES

Troffer is ideal for all commercial and industrial buildings requiring general illumination with recessed configurations.

- Low-profile which meets limitless range of applications.
- Use 30% less energy than a linear fluorescent fixture.
- · Smooth edges for easy handling.
- Diffusing lens gives soft even light.

MOUNTING

- · Recessed ceiling mount
- · Exposed T-grid ceiling

APPLICATION

Ideal for offices, retail, commercial buildings and work areas.

ELECTRICAL

Wattage	42W	
Voltage	120-277V	
Power Factor	0.9	
Total Harmonic Distortion (THD)	10	
LIGHTING PERFORMANCE		
Lumens	4536	
Lumens Per Watt (LPW)	108	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	80	
R9 (Red Value)	N/A	
R13 (Skin Tones)	N/A	
Beam Angle	100°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B2 - U2 - G1	
Dimmable Lighting Control	(Dimmable 0-10V, Range 10% - 100%	
ENVIRONMENT		
Operating Temperature	-4° ~ 122°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP40	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	
COMPONENTS		
LED Light Source	Seoul 3528	
Driver	Simon SI50-I1000	
CONSTRUCTION		
Housing	24 Gauge C.R.S.	
Lens	Prismatic	
Base / Power Supply	Hard Wired	
Finish	White	

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: **55272 LED 2X4 RECESSED TROFFER**



DIMENSIONS (Inches)

Length	47.6"
Width	23.8"
Height	3.6"
Net Weight (Lbs)	

Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768026160	50" x 25" x 4"	18.2
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55272	LED 2X4 TR0FFER/42W/40K/DIMM/120-277V - 5.0	1
ACCESSORIE	s	
55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN- INTEGRATION TYPE - T20C	6
55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN- INTEGRATION TYPE - T20C	6
55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN- INTEGRATION TYPE - T20C	6
REPLACEMEN	NT PARTS	
552728	REPLACEMENT LENS	1
SI50-I1000	REPLACEMENT DRIVER	1