



SELECTABLE
COLOR
TEMPERATURE

Item#: 55506 LED 2' TONE-SELECT™ LINEAR HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL
AND INDUSTRIAL BUILDINGS

FEATURES

- Selectable color temperature
- High lumen output - bright and high lumen per watt.
- Integrated LED - maintenance free.
- Replaces HID and fluorescent fixtures.
- Wide beam angle - uniform light distribution.
- All steel surfaces are painted after fabrication for smooth edges and rounded corners.

MOUNTING

Designed for suspended or pendent mounting.

APPLICATION

Larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	130W
Voltage	120-277V
Current	1.08A
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	17550
Lumens Per Watt (LPW)	135
Color Temperature (CCT)	4000K / 5000K
Color Rendering (CRI)	80
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	120°
Light Distribution	--
BUG Rating (Backlight, Uplight, and Glare)	--
Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-4° ~ 122°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Bridgelux
Driver	Simon

CONSTRUCTION

Housing	24 Gauge C.R.S.
Lens	Acrylic (PMMA)
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

PERFORMANCE DATA


Item#: **55506**
LED 2' TONE-SELECT™ LINEAR HIGH BAY



ITEM INFORMATION

DIMENSIONS (Inches)

Length	23.8"
Width	13"
Height	3.6"
Net Weight (Lbs)	10.1
Chain Length	41.34" (2 ea.)



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	811768022933	--	--
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
55506	LED 2FT TONE-SELECT™ LINEAR HIGH BAY/130W/40-50K/DIMM/120-277V	1

ACCESSORIES

55220	3.3" PENDENT MOUNT FOR STANDARD LINEAR HIGH BAY (1/2" THREADED HOLE)	25
54896	360° LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30' DIA, 8-40' HEIGHT 800W/1200W - 120/277V	50
54897	360° LOW BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 48' DIA, 8-20' HEIGHT 800W/1200W - 120/277V	50
54898	360° HIGH BAY BI-LEVEL AND DAYLIGHT HARVEST MICROWAVE SENSOR 60' DIA, 8-50' HEIGHT 800W/1200W - 120/277V	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898	100
55319	EMERGENCY PACK FOR LED FIXTURE 8W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
55320	EMERGENCY PACK FOR LED FIXTURE 16W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
55321	EMERGENCY PACK FOR LED FIXTURE 25W/90 MIN/INTEGRATION TYPE - T20C (For use with drivers that are 100W or less.)	6
45002	100' ROLL NO. 12 JACK CHAIN	Per Foot

REPLACEMENT PARTS

--	LED REPLACEMENT DRIVER	1
----	------------------------	---

ADDITIONAL INFORMATION:

Note: When using an Emergency Pack with the fixture, cable mounting is recommended to control the balance of the fixture.