



Item#: **PL55548A**
LED 4' ARCHITECTURAL STRIP
DIRECT LINEAR AMBIENT LUMINARIES

FEATURES

- Low-profile with a limitless range of applications.
- Uses 30% less energy than a linear fluorescent fixture.
- Energy efficient
- No flickering

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Wattage	35W
Voltage	120-277V
Power Factor	0.9
Total Harmonic Distortion (THD)	10

LIGHTING PERFORMANCE

Lumens	4620
Lumens Per Watt (Lm/W)	130
Color Temperature (CCT)	5000K
Color Rendering (CRI)	82
Beam Angle	130°

Dimmable Lighting Control	<i>Dimmable</i> 0-10V, Range 10% - 100%
---------------------------	--

ENVIRONMENT

Operating Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP40

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

CONSTRUCTION

Housing	Aluminum
Lens	Frosted
Base / Power Supply	Hard Wired
Finish	White

DIMENSIONS (Inches)

Length	48"
Width	3.4"
Height	3.6"

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

ORDERING

ITEM#	DESCRIPTION	CASE
PL55548A	LED 4FT ARCHITECTURAL DESIGNER STRIP/35W/50K/DIMM/120-277V	6
PL55548A-MS	LED 4FT ARCHITECTURAL DESIGNER STRIP/35W/50K/DIMM/120-277V/SENSOR	6
PL55548-8WEMA	LED 4FT ARCHITECTURAL DESIGNER STRIP/35W/50K/DIMM/120-277V/8W EM BATTERY	6
PL55548-8WEMA-MS	LED 4FT ARCHITECTURAL DESIGNER STRIP/35W/50K/DIMM/120-277V/8W EM BATTERY/SENSOR	6