



Item#: 55624
LED 4' STRIP FIXTURE
LED READY FIXTURE

FEATURES

- Use 30% less energy than a traditional fluorescent fixture
- · Die formed, and rigidly fabricated
- · LED ready with non-shunted sockets
- Pre-wired for Double-End Type B Direct Wire and Type C tubes
- Designed for surface or chain mounting

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Lamp Type (not included)	T5
Number of Lamps	2
Voltage	120-277V

ENVIRONMENT

LITAIIIOMMENT	
Operating Temperature	-13° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

LIFESPAN

Warranty (Years)	2

CONSTRUCTION

Housing	Galvanized Sheet Metal	
Base / Power Supply	Hard Wired	
Finish	Baked White Enamel	

QUALIFICATIONS



 ${\it Operating temperature may vary depending on the lamps used. \bullet Specifications are subject to change \it without notice.}$

Item#: **55624**LED 4' STRIP FIXTURE



DIMENSIONS (Inches)

Length	48.6"
Width	2.8"
Height	1.8"
Weight (Lbs)	

	48.3" —	Ц
• .	0-	D•
_*U	2.8"	<u></u>

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	6	10854432004474	49.8" x 10.5" x 5"	23.1
Individual Box	1	854432004477	49" x 3.2" x 2"	3.9
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
55624	LED 4FT STRIP FIXTURE FOR 2 T5	6
ACCESSORII	ES	
54896	LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30FT DIA, 8-40FT HEIGHT 800W/1200W • 120/277V	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898	100
55639	ADJUSTABLE WALL MOUNTING BRACKET FOR STRIP FIXTURE/WHITE/SET OF 2	1

ADDITIONAL INFORMATION:

• Pairs with Direct Wire Double-End UL Type B or UL Type C Lamps. Follow specific lamp installation wiring instructions for correct wiring.