



Item#: 55625 LED 8' TANDEM STRIP FIXTURE LED READY FIXTURE

FEATURES

- Use 30% less energy than a traditional fluorescent fixture
- · Die formed, and rigidly fabricated
- · LED ready with non-shunted sockets
- Pre-wired for Double-End Type B Direct Wire and Type C tubes
- Designed for surface or chain mounting

APPLICATION

Ideal for larger warehouses, retail applications, commercial buildings and work areas.

ELECTRICAL

Lamp Type (not included)	T5
Number of Lamps	4
Voltage	120-277V

ENVIRONMENT

LITALIIOMIILMI	
Operating Temperature	-13° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

LIFESPAN

Warranty (Years)	2
------------------	---

CONSTRUCTION

Housing	Galvanized Sheet Metal	
Base / Power Supply	Hard Wired	
Finish	Baked White Enamel	

QUALIFICATIONS




Operating temperature may vary depending on the lamps used. - Specifications are subject to change without notice.

Item#: **55625**LED 8' TANDEM STRIP FIXTURE



DIMENSIONS (Inches)

Length	96.7"
Width	2.8"
Height	1.8"
Weight (Lbs)	



SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet VIEW			
Install Instructions	VIEW		

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	4	10811768020721	97.6" x 6.9" x 5"	30.3
Individual Box	1	811768020724	97.5" x 3.2" x 2"	7.6
Country of Origin	China			
HS Tariff				

ORDERING

ITEM#	DESCRIPTION	CASE
55625	LED 8FT TANDEM STRIP FIXTURE FOR 4 T5	4
ACCESSORI	ES	
54896	LOW/HIGH BAY FIXTURE OCCUPANCY PIR SENSOR 30FT DIA, 8-40FT HEIGHT 800W/1200W • 120/277V	50
54894	EXTENDER MOUNT FOR SENSOR 54896/54897/54898	100
55639	ADJUSTABLE WALL MOUNTING BRACKET FOR STRIP FIXTURE/WHITE/SET OF 2	1

ADDITIONAL INFORMATION:

• Pairs with Direct Wire Double-End UL Type B or UL Type C Lamps. Follow specific lamp installation wiring instructions for correct wiring.