



Item#: **55703 LED 8W EMERGENCY PACK** FOR LED INDOOR FIXTURES

FEATURES

- Kit includes; an LED emergency pack and test light indicator
- Slim profile and easy installation
- High efficiency
- Constant output power
- Self test
- Short circuit, over voltage and over temperature protection

APPLICATION

For use in LED Designer Strip and Vapor Tight Fixtures.

OUTPUT		
Output Power	8W	
Output Voltage	30-60V DC	
INPUT		
Input Power	8W Max.	
Input Current	≤100mA Max.	
Input Voltage	100-347V • 50/60Hz	
PERFORMANCE		
Emergency Time	90 Min.	
Recharge Time Required	≥24 Hours	
Battery Type	Lithium	
ENVIRONMENT		
Ambient Temperature	41° ~ 122°F	
Suitable Location	DAMP	
Max. Mounting Height	16.5FT	
LIFESPAN		
Warranty (Years)		



Meets Standard(s) for Safety UL 924 · Specifications are subject to change without notice.

PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107 © P.Q.L., Inc. · 2285 Ward Avenue · Simi Valley, CA 93065


Item#: **55703** LED 8W EMERGENCY PACK



DIMENSIONS (Inches)

Length	12.5″
Width	1.3"
Height	0.8"
Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	20	10811768025818	17.3" x 14.2" x 11.8"	
Individual Box	1	811768025811	14.3" x 2.6" x 1.4"	
Country of Origin	China			
HS Tariff	-			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
55703	EMERGENCY PACK FOR SLIM LED STRIP/VAPOR TIGHT 8W/90 MIN		10
ACCESSORIES	5		
55697	DUAL COLOR TAPE TEST BUTTON AND ADAPTOR FOR EMERGENCY BATTERY TROFFER OR PANEL		400

ADDITIONAL INFORMATION:

• An un-switched AC power source is required.

This device is designed for use in fixtures listed for dry and damp locations.