

GO-LED™ SEAMLESS

Architectural LED Luminaire

Client: _____ Order #: _____
Project Name: _____ Type: _____ Qty: _____

Performance Data

CRI

80+

Tone- Select™ - CCT Selectable

3500K, 4000K, 5000K

Projected Lifetime

>50,000 Hours

Dimming

0-10V Dimming Standard,
10% to 100%

Operating Temperature


-4° to 104°F

Safety Listed

UL, Suitable for dry and damp locations; IC-rated

Warranty

5 year Standard
10 year Optional



Description

Introducing the GO-LED™ Fixture: a design-driven solution for upgrading fluorescent troffers. Perfect for commercial spaces like offices, classrooms, healthcare facilities, and retail areas. Our GO-LED™ Fixtures come standard with dimmable capabilities and boast market-leading LED technology, reaching up to 125 lumens per watt in efficiency. Crafted with top-notch components, these fixtures ensure consistent and balanced lighting. The main diffuser and slanted troffer design minimize glare, providing soft and comfortable illumination. With their appealing aesthetics and simple installation, the GO-LED™ Fixture family can effortlessly transform any space in minutes.

Features

- High reflectance optical engine delivers main beam focus through the optically designed acrylic lens.
- Linear acrylic lens manages the balance of efficiency and aesthetics.
- Delivers efficacy of up to 125 lm/W
- Linear arrayed LED modules provide soft, but effective illumination.
- Frosted acrylic lens easily removes for cleaning.
- Dimming (0-10V) and Architectural Narrow lens are standard.
- Spec-Select™ allows users to select between 4 wattages and 3 CCT (5000K, 4000K, and 3500K) in the field by simply switching an easily accessible switch. Fixture comes set/standard at lowest wattage and 40K.

Ordering Information

FIXTURE SERIES

GO-LED™ Architectural LED Fixture

2X2

#55780

#55780-8WEM with EM Installed

19W 2385LM

24W 3012LM

32W 4016LM

39W 4895LM

2X4

#55784

#55784-8WEM with EM Installed

29W 3654LM

34W 4284LM

39W 4926LM

49W 6189LM

CCT

354050 3500K-4000K-5000K

VOLTAGE

U 120-277V


OPTIONS

#83893 Emergency

#54895* PIR Sensor

#54886 Sensor Adapter

* 54895 requires adapter 54886 for proper installation.



WARRANTY¹

- 5 Year Warranty

10 10 Year Warranty

10L 10 Year Warranty including labor

¹ 5 Year Warranty is Standard unless specified

REPLACEMENT DRIVERS

2x2 557806

2x4 557846



Qualification Model #: 55780-[Blank,8WEM]-[Blank,MS,BT]



Qualification Model #: 55784-[Blank,8WEM]-[Blank,MS,BT]

Dimensions

	X ₁	X ₂	X ₃
2 x 2	23.8"	23.8"	2.2"
2 x 4	47.7"	23.8"	2.2"

