

# LED SPEC-SELECT™ STEALTH-TRAC HEAD - 8084X



DIMMING COMPATIBILITY

BRAND	MODEL	ILED (mA)		DIMMING RANGE (%)		1 LAMP / DIMMER					3 LAMPS / DIMMER					5 LAMPS / DIMMER					NOISE TEST RESULT	
		MAX	MIN	MAX	MIN	MAX	75%	50%	25%	MIN	MAX	75%	50%	25%	MIN	MAX	75%	50%	25%	MIN		
COOPER	MLV-600	939	27	98.8	2.84	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
DIVA	DVCL-153P	858	0	90.3	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
	DVELV-300P	880	46	92.6	4.8	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
LEVITON	6613-P	940	18	98.9	1.89	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
	6633-P	942	0	99.1	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
	IP106 <sup>1</sup>	933	0	98.2	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
	IP1106 <sup>1</sup>	935	0	98.4	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
MAESTRO	MS-OP600G	740	17	77.9	1.78	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
SKYLARK	CTCL-153P	866	0	91.1	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
	S-600	926	0	97.4	0	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A
TOGGLER	TGCL-153P	867	25	91.2	2.6	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	A

1: Turning on the dimmer at the lowest level and dimming up, fixtures didn't light on synchronized.

KEY											
DIMMING RATIO	MAX	Highest Level		✓	Pass (No Flicker)	✗	Failed (Flicker)	SF	Slight Flicker	A	Noise Test: Distance 3.9"
	MIN	Lowest Level								B	Noise Test: Distance 7.9"
	75%, 50%, 25%	Dimming Ratio according to output current.								C	Noise Test: Distance 11.8"