

ELECTRICAL

Wattage	36W		
Voltage	120V		
LIGHTING PERFORMANCE			
Lumens	2400		
Lumens Per Watt (Lm/W)	67		
Color Temperature (CCT)	3000K		
Color Rendering (CRI)	80		
Dimmable Lighting Control			


LIFESPAN

Average Life (Hours)	36,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass / Plastic		
Base / Power Supply	2G11		
Finish	White		
Mercury Content 🐵	2.2mg		

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



SUPPORTING DOCUMENTS

DIMENSIONS (Inches)

Width/Diameter (MOD)

Length (MOL)

Net Weight (Lbs)

Item#: **81752** 36W PLL - 4 PIN

COMPACT FLUORESCENT

Excellent color rendition
Light instantly, no flicker

· Light weight and has a low profile

FEATURES

APPLICATION

Product Sheet	VIEW
---------------	------

- Less heat output with a low starting temperature

Available in a full selection of sizes and designs that

allow a convenient fit for nearly every style of fixture.

16.5"

1.7"

--

Used for decorative and orientation lighting.

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50		17.7" x 11" x 9.8"	16.3
Individual Box	1			0.33
Country of Origin	China			
HS Tariff	8539.31.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
81752	PLL36/30K/2G11 4 PIN - SUPERIOR LIFE®	50

ADDITIONAL INFORMATION:

Family Item(s): 81754/3500K • 81756/4100K

PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065