

ELECTRICAL

Wattage	40W		
Voltage	120V		
LIGHTING PERFORMANCE			
Lumens	2800		
Lumens Per Watt (LPW)	70		
Color Temperature (CCT)	3000K		
Color Rendering (CRI)	80		
Dimmable Lighting Control			


LIFESPAN

Average Life (Hours)	36,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass / Plastic	
Base / Power Supply	2G11	
Finish	White	
Mercury Content 🐵	2.2mg	

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



SUPPORTING DOCUMENTS

DIMENSIONS (Inches)

Width/Diameter (MOD)

Length (MOL)

Net Weight (Lbs)

Item#: 81758 40W PLL - 4 PIN

COMPACT FLUORESCENT

Excellent color rendition
Light instantly, no flicker

· Light weight and has a low profile

- Less heat output with a low starting temperature

Available in a full selection of sizes and designs that

allow a convenient fit for nearly every style of fixture.

22.5"

1.7"

--

Used for decorative and orientation lighting.

FEATURES

APPLICATION

Product Sheet	VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50		23.6" x 11" x 9.8"	25.1
Individual Box	1	811768020366		0.50
Country of Origin	China			
HS Tariff	8539.31.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
81758	PLL40/30K/2G11 4 PIN	50

ADDITIONAL INFORMATION:

Family Item(s): 81760/3500K • 81762/4100K • 81764/5000K

PREMIUM QUALITY LIGHTING® - Phone: 800-323-8107

© P.Q.L., Inc. • 2285 Ward Avenue • Simi Valley, CA 93065