



FEATURES

- · Light weight and has a low profile
- · Excellent color rendition

COMPACT FLUORESCENT

- · Light instantly, no flicker
- Less heat output with a low starting temperature

APPLICATION

Available in a full selection of sizes and designs that allow a convenient fit for nearly every style of fixture. Used for decorative and orientation lighting.

| DIM | CNC | IANC | /I I \ |
|-----|-----|------|----------|
| DIN | FN2 | IUN5 | (Inches) |

| Length (MOL) | 21.2" |
|----------------------|-------|
| Width/Diameter (MOD) | 1.7" |
| Net Weight (Lbs) | |

SUPPORTING DOCUMENTS

| Product Sheet | VIEW |
|---------------|------|
|---------------|------|

| ELECTRIC | AL |
|----------|----|
| | |

| Wattage | 55W |
|---------------------------|-------------|
| Voltage | 120V |
| LIGHTING PERFORMANCE | |
| Lumens | 3900 |
| Lumens Per Watt (LPW) | 71 |
| Color Temperature (CCT) | 3500K |
| Color Rendering (CRI) | 80 |
| Dimmable Lighting Control | COT COMMAND |
| | |


LIFESPAN

| Average Life (Hours) | 36,000 |
|----------------------|--------|
| Warranty (Years) | 1 |

CONSTRUCTION

| Housing | Glass / Plastic | |
|---------------------|-----------------|--|
| Base / Power Supply | 2G11 | |
| Finish | White | |
| Mercury Content (9) | 2.2mg | |

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|----------------|---------------------------|--------------------|
| Master Carton | 50 | 10811768023999 | 23.2" x 12.2" x 10.2" | 20.3 |
| Individual Box | 1 | 811768023992 | | 0.41 |
| Country of Origin | China | | | |
| HS Tariff | 8539.31.0050 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|-------|----------------------|------|
| 81766 | PLL55/35K/2G11 4 PIN | 50 |