



Item#: **81806**
26W PLC - 4 PIN
COMPACT FLUORESCENT

FEATURES

- Light weight and has a low profile
- Excellent color rendition
- Light instantly, no flicker
- Less heat output with a low starting temperature

APPLICATION

Available in a full selection of sizes and designs that allow a convenient fit for nearly every style of fixture. Used for decorative and orientation lighting.

DIMENSIONS (Inches)

Length (MOL)	6.5"
Width/Diameter (MOD)	1.4"
Net Weight (Lbs)	--

SUPPORTING DOCUMENTS

Product Sheet	VIEW
---------------	------

PACKAGING

Master Carton	200
Inner Carton	50
Individual Box	1
Country of Origin	China
HS Tariff	8539.31.0050

ORDERING

ITEM#	DESCRIPTION	CASE
81806	PLC26/27K/G24Q-3 4 PIN	200


ADDITIONAL INFORMATION:

Family Item(s): 81808/3000K • 81810/3500K • 81812/4100K • 81813/5000K

ELECTRICAL

Wattage	26W
Voltage	120V

LIGHTING PERFORMANCE

Lumens	1560
Lumens Per Watt (LPW)	60
Color Temperature (CCT)	2700K
Color Rendering (CRI)	80
Dimmable Lighting Control	

LIFESPAN

Average Life (Hours)	12,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass / Plastic
Base / Power Supply	G24Q-3
Finish	White
Mercury Content (µg)	2.2mg

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

