



Item#: 81815 26W PLT - 4 PIN COMPACT FLUORESCENT

FEATURES

- · Light weight and has a low profile
- · Excellent color rendition
- · Light instantly, no flicker
- Less heat output with a low starting temperature

APPLICATION

Available in a full selection of sizes and designs that allow a convenient fit for nearly every style of fixture. Used for decorative and orientation lighting.

D	IM	E۱	ISI	0	NS	(Inc	hes)
---	----	----	-----	---	----	------	------

Length (MOL)	5.2"
Width/Diameter (MOD)	1.8"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS

Product Sheet	VIEW
---------------	------

ELECTRICAL

Wattage	26W
Voltage	120V
LIGHTING PERFORMANCE	
Lumens	1560
Lumens Per Watt (LPW)	60
Color Temperature (CCT)	2700K
Color Rendering (CRI)	80
Dimmable Lighting Control	


LIFESPAN

Average Life (Hours)	12,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass / Plastic		
Base / Power Supply	GX24Q-3		
Finish	White		
Mercury Content (19)	2.2mg		

Published lumens are approximate and may vary slightly. Specifications are subject to change without notice. This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	100	10854432004870	18.9" x 11" x 13"	23.2
Inner Carton	25	20854432004877		5.8
Individual Box	1	854432004873		0.23
Country of Origin	China			
HS Tariff	8539.31.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
81815	PLT26/27K/GX24Q-3 4 PIN	100

ADDITIONAL INFORMATION:

Family Item(s): 81817/3000K - 81818/3500K - 81819/4100K