

82205 LED GREEN UNIV EXIT SIGN

EMERGENCY EXIT SIGNS & LIGHTING





TECHNICAL DATA SHEET

FEATURES

- Innovative, snap-together design allows for fast and easy installation
- · Replaceable directional chevron inserts are easily removed and reinserted
- LED lamps are operating in normal (AC input) and emergency (DC input) modes.
- Housing snaps to canopy with simple twist and tightly locks the housing and canopy.
- UL 5VA flame rating


APPLICATION

Emergency exit lighting is used in a wide variety of places such as; movie theatres, commercial buildings, restaurants, and hotels.

PRODUCT DETAILS

ELECTRICAL	
Wattage	2W
Voltage	120/277V
COMPONENTS	
Battery	Nickel - Cadmium
Discharge Time	90 Minutes
Recharge Time	24 Hours
CONSTRUCTION	
Housing	Thermoplastic ABS
Base / Power Supply	Hard Wired
Finish	White
Surface	Single or Double
Lettering	Green - 6"(H)
Mounting	Universal (Wall, Side, or Ceiling)
ENVIRONMENT	
Operating Temperature	10°C ~ 40°C
Suitable Location	DAMP Indoor / Covered Ceilings
Ingress Protection Rating	IP43
CERTIFICATIONS	

LIFESPAN	
Warranty (Years)	3
PACKAGING	
Master Carton	12pc / 10811768023432
Individual Box	811768023435
Country of Origin	China
HS Tariff	9405.60.6000
DIMENSIONS	
Dimensions (Inches)	11.8"(L) x 7.3"(W)





ORDERING

ITEM#	DESCRIPTION	CASE
82205	LED GREEN UNIV EXIT SIGN - BATTERY BACKUP	12