

82228 Outdoor die Cast Emergency light

EMERGENCY EXIT SIGNS & LIGHTING

PRODUCT DETAILS



FEATURES

- Architectural, low profile design
- Test swith and charge rate indicator
- Polycarbonate lens and mirror reflector
- Low voltage battery disconnection preventing deep discharge damage to the battery
- UL 94V-0 flame rating.

APPLICATION

Emergency exit lighting is used in a wide variety of places such as; movie theatres, commercial buildings, restaurants, and hotels.

ELECTRICAL	
Wattage	6W
Voltage	120/277V
Lumens	121
COMPONENTS	
Battery	Nickel Cadmium (6V 5A)
Discharge Time	90 Minutes
Recharge Time	24 Hours
Emergency Lamps	(2) 6V 6W Xenon Lamp
CONSTRUCTION	
Housing	Die Cast Aluminum
Base / Power Supply	Hard Wired
Finish	Bronze
Mounting	Wall or Ceiling
ENVIRONMENT	
Operating Temperature	0°C ~ 50°C
Suitable Location	WET
Ingress Protection Rating	IP65
CERTIFICATIONS	
N/A	

LIFESPAN	
Warranty (Years)	1
PACKAGING	
Master Carton	6pc / 10811768024743
Individual Box	811768024746
Country of Origin	China
HS Tariff	9405.60.6000
DIMENSIONS	
Dimensions (Inches)	10.5"(L) X 6.5"(W)
10.5"	

6.5'

⊢ 3.8″ ⊣

ORDERING

ITEM#	DESCRIPTION	CASE
82228	OUTDOOR DIE CAST EMERGENCY LIGHT, 6W XENON LAMP, DARK BRONZE HOUSING/WITH SELF-DIAGNOSTIC FUNCTION	6