

83216 LED MINI WALL PACK/17W

TECHNICAL DATA SHEET



FEATURES



Outdoor Wall-Mounted Area Luminaires

- Easy installation
- Replaces 25W HID

HOUSING

- Sealed die-casting profile for outdoor applications.
- Polycarbonate optical lens with UV stabilizers.
- · Damp and Wet Locations

APPLICATION


- · Security, pathway and perimeter lighting
- Building entry ways and walkways







SPECIFICATIONS							
Power Consumption	17W						
Input Voltage	120-277V						
Power Factor	0.9						
Lumens	1685						
Luminous Efficiency	96 Lm/W						
Color Temperature	4000K						
CRI	83						
Housing	Die-Cast Aluminum						
Lens	PC Cover						
Finish	Bronze						
Dimensions (Inches)	8.4"(L) x 5.5"(W) x 3.2"(D)						
LIFESPAN & ENVIRONMENT							
Average Life	50,000						
Operating Temperature	-25°C ~ 40°C						
DIMENSIONS							



ORDERING

ITEM#	DESCRIPTION	WATTS	COLOR	LUMENS	CRI	VOLTS	HOUSING	HOURS	CASE
83216	LED MINI WALL PACK/BLACK/17W/40K/120-277V - SUPERIOR LIFE®	17	4000K	1685	83	120-277	BLACK	50,000	12