



Item#: 83233 **LED CANOPY PARKING GARAGE LUMINAIRES**

FEATURES

- · Ultra-thin design.
- Replaces 400W MH.

HOUSING

- Sealed die-casting profile for indoor applications.
- Polycarbonate optical lens with heat resisting.


MOUNTING

 Three 1/2" threaded conduit and one 3/4" conduit entry points.

APPLICATION

Parking structures and storage areas.

LIGHT DISTRIBUTION CURVE



| ELECTRICAL | | |
|--|---|--|
| Wattage | 65W | |
| Voltage | 100-277V | |
| Current | 0.541A | |
| Power Factor | 0.9 | |
| Total Harmonic Distortion (THD) | 13.8 | |
| LIGHTING PERFORMANCE | | |
| Lumens | 6600 | |
| Lumens Per Watt (Lm/W) | 101 | |
| Color Temperature (CCT) | 5000K | |
| Color Rendering (CRI) | 70 | |
| R9 (Red Value) | -14 | |
| R13 (Skin Tones) | 71 | |
| Beam Angle | 160° | |
| Light Distribution | Type VS | |
| BUG Rating (Backlight, Uplight, and Glare) | B2 - U2 - G2 | |
| Dimmable Lighting Control | (Dimmable 0-10V, Range 10% - 100% | |
| ENVIRONMENT | | |
| Operating Temperature | -13° ~ 104°F | |
| Suitable Location | WET | |
| Ingress Protection Rating | IP65 | |
| LIFESPAN | | |
| Average Life (Hours) | 50,000 | |
| Warranty (Years) | 5 | |
| COMPONENTS | | |
| LED Light Source | Cree CXA2 | |
| Driver | 52112 (75W Max.) | |
| CONSTRUCTION | | |
| Housing | Aluminum/PC | |
| Deser / Deserve Committee | 11 1.147 1 | |

QUALIFICATIONS

Finish



Base / Power Supply

Visit www.designlights.org/search to confirm qualifications. • Published lumens on LED products are approximate and may vary slightly.

Hard Wired

Black


Item#: 83233 **LED CANOPY**





DIMENSIONS (Inches)

Line drawings may not be to scale and are for general reference only.

| SUPPORTING DOCUMENTS (Grey = not available at this time.) | | | |
|--|------|--|--|
| Product Sheet | VIEW | | |
| Install Instructions | VIEW | | |
| Photometric | VIEW | | |
| IES Download from Web Item | VIEW | | |
| LM79 | VIEW | | |
| LM80 | VIEW | | |
| | | | |







| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|----------------|----------------------|--------------------|
| Master Carton | 6 | 10811768025948 | 10.6" x 10.6" x 3.9" | |
| Individual Box | 1 | 811768025941 | - | |
| Country of Origin | China | | | |
| HS Tariff | 9405.10.6020 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|---------|--|------|
| 83233 | LED CANOPY 65W/50K/100-277V/BLACK/DIMMABLE - SUPERIOR LIFE® DLC ® | 6 |
| ACCESSO | RIES/REPLACEMENT PARTS | |

| 832338 | REPLACEMENT LENS FOR CANOPIES | 1 |
|--------|-------------------------------|---|
| 52112 | REPLACEMENT DRIVER 75W | 1 |

ADDITIONAL INFORMATION:

*83233 is being replaced by 83346

Family Item: 83232/4000K

Note: To prevent water damage which may shorten the life of an exterior mounted fixture; the fixture should be properly weather sealed according to the installation instructions or between the fixture base and mounting surface. Damage due to improper installation may void the warranty.