



Item#: 83757 LED CEILING LIGHT INDOOR FIXTURE

FEATURES

- Diffusing lens provides glare free illumination and even light distribution.
- Designed with the lasted solid state lighting and electronic driver for optimal performance and energy efficiency.
- Die formed cold rolled steel mounting plate; painted with a treatment for anti-corrosion.

APPLICATION

Homes, schools, retail, office and hospitality.

ELECTRICAL

Wattage	17W
Voltage	120V
Current	0.15A
Power Factor	0.8
Total Harmonic Distortion (THD)	N/A
LIGHTING PERFORMANCE	
Lumens	1300

Lumens	1300
Lumens Per Watt (LPW)	76
Color Temperature (CCT)	4000K
Color Rendering (CRI)	80
R9 (Red Value)	25
R13 (Skin Tones)	87
Beam Angle	120°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1
Dimmable Lighting Control	Dimmable

ENVIRONMENT

Operating Temperature	-4° ~ 104°F
Suitable Location	DAMP
Ingress Protection Rating	IP20

LIFESPAN

Average Life (Hours)	35,000
Warranty (Years)	3

COMPONENTS

LED Light Source	Samsung SPMWHx228F
Driver	837546 - 16W320MAC

CONSTRUCTION

Housing	C.R.S / PC
Base / Power Supply	Hard Wired
Finish	White

QUALIFICATIONS







Visit www.energystar.gov to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: 83757 LED CEILING LIGHT



DIMENSIONS (Inches)

Length	10.6"
Width	10.6"
Height	3.3"
Net Weight (Lbs)	

Product Sheet VIEW Install Instructions VIEW Photometric VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	10	10811768029021	20.7" x 13.2" x 26.6"	
Individual Box	1	811768029024	11.9"x 3.8" x 12"	
Country of Origin	China			
HS Tariff	9405.10.6020			

ORDERING

ITEM#	DESCRIPTION	CASE
83757	LED 11IN SQUARE CEILING LIGHT/17W/40K/DIMM/120V/WHT - ENERGY STAR°	10
REPLACEM	IENT PARTS	
837578	11" SQUARE REPLACEMENT LENS COVER	1