



Item#: 83870 **LED TONE-SELECT™ DESIGNER SURFACE MOUNT**

INDOOR FIXTURE

FEATURES

- · Selectable color temperature
- · LED surface mount fixture provides glare free illumination and even light distribution with a clean, modern look.
- · Diffusing lens
- · Low profile design
- Title 24 JA8 Compliant

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, hallways, lobbies and other residential and commercial applications.

PREMIUM QUALITY LIGHTING®

LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	18W 120V 0.17A 0.9 1350 75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
Current Power Factor LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	0.17A 0.9 1350 75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
Power Factor LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	1350 75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
LIGHTING PERFORMANCE Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	1350 75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
Lumens Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dinmable see compatibility report	
Lumens Per Watt (LPW) Color Temperature (CCT) Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	75 30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dinmable see compatibility report	
R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	30K / 40K / 50K 90 120° Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	90 120° Type II, Very Short B1 - U1 - G1 "Dinmable see compatibility report	
Color Rendering (CRI) R9 (Red Value) Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours) Warranty (Years)	Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report	
Beam Angle Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report -4° ~ 104°F	
Light Distribution BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	Type II, Very Short B1 - U1 - G1 "Dimmable see compatibility report -4° ~ 104°F	
BUG Rating (Backlight, Uplight, and Glare) Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	B1 - U1 - G1 (Dimmable see compatibility report	
Dimmable Lighting Control ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	Dimmable see compatibility report	
ENVIRONMENT Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)	see compatibility report -4° ~ 104°F	
Operating Temperature Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)		
Suitable Location Ingress Protection Rating LIFESPAN Average Life (Hours)		
Ingress Protection Rating LIFESPAN Average Life (Hours)	DAMP	
LIFESPAN Average Life (Hours)	Indoor / Covered Ceilings	
Average Life (Hours)	IP20	
Warranty (Years)	50,000	
	5	
COMPONENTS		
LED Light Source	SMD 2835	
Driver	Internal	
CONSTRUCTION		
Housing		
Lens		
Base / Power Supply	Hard Wired	
Finish	White	



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.

Item#: **83870**LED TONE-SELECT™ DESIGNER SURFACE MOUNT




DIMENSIONS (Inches)

Width/Diameter (MOD)	8.9"		
Height	0.5"		
Net Weight (Lbs)	1.2		

SUPPORTING DOCUMENTS (Grev = not available at this time.)

GOTT GITTING BOOGHIZHTO (Grey - not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
Dimmer Compatibility	VIEW	
IES Download from Web Item	VIEW	
LM80	VIEW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	20	10811768029687	16.5" x 14.6" x 15.4"	30.9
Individual Box	1	811768029680	9.6" x 9.1" x 1.3"	1.5
Country of Origin	China			
HS Tariff	9405.99.4090			

ORDERING

ITEM#	DESCRIPTION	JA8	CASE
83870	LED 9IN TONE-SELECT™ DESIGNER SURFACE MOUNT/18W/30-40-50K/DIMM/120V/WHT/RND	Yes	20
ACCESSORIES			
83872	5/6IN DOWNLIGHT E26 MOUNTING ACCESSORY FOR 7 OR 9IN DESIGNER SURFACE MOUNTED FIXTURES		100