



Item#: **90383**

LED COMPASS HIGH BAY

HIGH-BAY LUMINAIRES FOR COMMERCIAL AND INDUSTRIAL BUILDINGS

FEATURES

- Die cast aluminum for better heat dissipation.
- Dust proof and anti-corrosive.
- Elegant design.
- High efficiency Meanwell constant-current driver.

APPLICATION

Ideal for commercial and industrial applications; malls, warehouses, factories, retail stores, athletic facilities, workshops, airports, and large areas.

ELECTRICAL

Wattage	307W
Voltage	100-277V
Power Factor	0.9
Total Harmonic Distortion (THD)	13.9

LIGHTING PERFORMANCE

Lumens	40239
Lumens Per Watt (Lm/W)	131
Color Temperature (CCT)	5000K
Color Rendering (CRI)	82
R9 (Red Value)	17
R13 (Skin Tones)	87
Beam Angle	120°
Light Distribution	Type VS
Dimmable Lighting Control	<i>Dimmable</i> 1-10V, Range 10% - 100%

ENVIRONMENT

Operating Temperature	-22° ~ 122°F
Suitable Location	WET
Ingress Protection Rating	IP65

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Luxeon 3030
Driver	Meanwell HLG-320H-48AB

CONSTRUCTION

Housing	Aluminum
Lens	Tempered Glass
Base / Power Supply	Hard Wired
Finish	Black

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly.

PERFORMANCE DATA

PACKAGING

Item#: **90383**
LED COMPASS HIGH BAY




DIMENSIONS (Inches)

Length	12.6"
Width/Diameter	12.6"
Height	6.3"
Weight (Lbs)	15

Line drawings may not be to scale and are for general reference only.

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	1	899645001363	15.8" x 15.8" x 15.8"	15.6
Country of Origin	China			
HS Tariff	9405.40.8200			

ORDERING


ITEM#	DESCRIPTION	CASE
90383	LED COMPASS HIGH BAY 300W/50K/100-277V/DIMMABLE - SUPERIOR LIFE® DLC®	1

ACCESSORIES/REPLACEMENT PARTS

90372	ADJUSTABLE ANGLE MOUNTING BRACKET FOR COMPASS HIGH BAY - SUPERIOR LIFE®	20
90370	MICROWAVE MOTION SENSOR FOR COMPASS HIGH BAY/100-277V 1-10V DIMM/KIT	10
90360	16" ALUMINUM REFLECTOR FOR COMPASS HIGH BAY - SUPERIOR LIFE®	1
90362	16" ACRYLIC REFLECTOR FOR COMPASS HIGH BAY - SUPERIOR LIFE®	1
90363	16" ACRYLIC BOTTOM LENS FOR ACRYLIC REFLECTOR FOR COMPASS HIGH BAY - SUPERIOR LIFE®	1
90396	78" WATERPROOF CONNECTOR AND CORD/BLACK 18AWG/300V - SUPERIOR LIFE®	50
HLG-320H-48AB	REPLACEMENT 320W CONSTANT VOLTAGE + CONSTANT LED DIMMABLE DRIVER	1

ADDITIONAL INFORMATION:

- Safety rope length approximately 5' 9"
- Power and dimming cord length approximately 8"
- Multiple screw holes are conveniently placed throughout the top of the fixture to connect occupancy sensors and reflectors.
- Hook dimensions (Screw M12):



PERFORMANCE DATA

PACKAGING