



# 90421

## LED LINEAR HYBRID T8


DUAL MODE INTERNAL DRIVER  
(UL TYPE A AND TYPE B)

The LED T8 Linear Hybrid tubes provides exceptional lighting with reduced energy and maintenance costs. The hybrid tube works with or without a ballast, making it a top-of-the-line replacement for standard fluorescent lamps.

- **DIRECT WIRE OR PLUG & GO™** - Simple rewiring installation allows lamps to run off main or use it with an instant start ballast as a plug and go.
- Wide beam design - 240° light emitting area
- Exceptional efficacy
- No flickering


**Note:** Non-shunted sockets are required for direct wire installation. See install instructions for further details.

### PRODUCT DETAILS

ELECTRICAL	
Wattage	15W
Voltage	120-277V
Current	150mA
Power Factor	0.9
Total Harmonic Distortion (THD)	10.8
LIGHTING PERFORMANCE	
Lumens	2000
Lumens Per Watt (Lm/W)	112
Color Temperature (CCT)	3500K
Color Rendering (CRI)	83
Beam Angle	160°
Light Distribution	Type VS
Dimmable Lighting Control	
ENVIRONMENT	
Operating Temperature	-20°C ~ 45°C
Suitable Location	<b>DAMP</b>
Ingress Protection Rating	IP20
CERTIFICATIONS	



LIFESPAN	
Average Life (Hours)	50,000
Warranty (Years)	<b>5</b>
COMPONENTS	
LED Light Source	Lextar PC35H11.V0
Driver	N/A
CONSTRUCTION	
Housing	Frosted Glass / Plastic End Caps
Base / Power Supply	G13 - Medium Bi Pin
Lens	Frosted / Safety Coated
PACKAGING	
Master Carton	25pc / 10811768020653
Individual Box	811768020656
Country of Origin	China
HS Tarrif	9405.40.8200
DIMENSIONS	
Dimensions (Inches)	48"(L) x 1"(DIA)



### ORDERING

ITEM#	DESCRIPTION	CASE
90421	LED SMD 4' 15WT8/35K/FR/SUPER HYBRID/SAFETY COATED V5 - SUPERIOR LIFE®	25

Note: DLC lists the wattage of the system power.

Published lumens on LED products are approximate and may vary slightly.