



Item#: 90736 **LED DIRECT WIRE LINEAR T8**

INTERNAL DRIVER LAMP-STYLE RETROFIT KITS (UL TYPE B)

FEATURES

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

SINGLE ENDED DIRECT WIRE

- · No ballast required, lamp runs off main
- Exceptional efficacy

*Non-shunted sockets required, see install instructions for further details.

ELECTRICAL

ELECINICAL		
Wattage	12W	
Voltage	120-277V	
Current	160-80mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	20	
LIGHTING PERFORMANCE		
Lumens	1400	
Lumens Per Watt (LPW)	117	
Color Temperature (CCT)	3500K	
Color Rendering (CRI)	82	
R9 (Red Value)	16	
R13 (Skin Tones)	N/A	
Beam Angle	210°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	B1 - U3 - G1	
Dimmable Lighting Control	See Install Instructions	
ENVIRONMENT		
Operating Temperature	-13° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	
LIFESPAN		
	50,000	
Average Life (Hours)	50,000 5	
LIFESPAN Average Life (Hours) Warranty (Years) COMPONENTS		
Average Life (Hours) Warranty (Years) COMPONENTS		
Average Life (Hours) Warranty (Years) COMPONENTS	5	
Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source CONSTRUCTION	5	
Average Life (Hours) Warranty (Years) COMPONENTS LED Light Source	5 Everlight 67-21S	



Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


Item#: 90736 LED DIRECT WIRE LINEAR T8



DIMENSIONS (Inches)

Length (MOL)	36"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)			
Product Sheet	VIEW		
Install Instructions	VIEW		
IES Download from Web Item	VIEW		
LM79	VIEW		
LM80	VIEW		



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768028307	37.8" x 7.9" x 7.9"	11.9
Individual Box	1	811768028300		
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
90736	LED 3FT 12WT8/35K/TYPE B/SE - DLC°	25
ACCESSORIES		
90405	LED 5W/90MIN. EMERGENCY BATTERY BACKUP FOR (1) T8 DIRECT WIRE LAMP 120/277V - T20C	25

ADDITIONAL INFORMATION:

Family Item(s): 90735/3000K • 90737/4000K • 90738/5000K

• PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.