

IESNA LM-79: 2008

Measurement and Test Report

for

Hengdian Group Tospo Lighting Co.,Ltd

Hengdian Electronics Industrial Zone,Dongyang,Zhejiang

Aug 14, 2015

Product Name:	LED
Model No:	694795
Test Engineer:	David Zhang 
Report No.:	BTR66.181.14.0051.14-1
Sample Received Date:	Jan 22, 2015
Test Performed Date:	Jan 22, 2015 to Jan 28, 2015
Reviewed By:	Steven Hsu 
Prepared By:	BEST Test Service Shenzhen Co., Ltd. 1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyan, Baoan, Shenzhen, China TEL: +86-755-28236006 FAX: +86-755-23467087-811 Email: certification@bestcert.cn



Note: This report is not valid as a BEST Test Report unless signed by an approved BEST Test Service Shenzhen Co., Ltd. This report shall not be reproduced except in full without the written approval of the testing laboratory. The test report only allows to be revised within the retention period unless further standard or the requirement was noticed. This report is for the exclusive use of BEST's Client and is provided pursuant to the agreement between BEST and its Client. BEST's responsibility and Liability are limited to the terms and conditions of the agreement. BEST assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the BEST name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by BEST. The observations and test results in this report are relevant only to the sample tested. This report by itself does not cover that the material, product, of service is or has ever been under a BEST certification program. National Voluntary Laboratory Accreditation Program (NVLAP) has accredited this laboratory under ISO17025: 2005 for specific laboratory activities as listed in the NVLAP directory of accredited laboratories. The results shown in this report were determined by this laboratory in accordance with its terms of accreditation. This report must not be used by the client to claim product endorsement by NVLAP, NIST or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION.....3

- 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)3
- 1.2 OBJECTIVE3
- 1.3 TEST FACILITY DESCRIPTION.....4
- 1.4 TEST EQUIPMENT LIST4

2 - TEST METHOD.....5

- 2.1 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (INTEGRATED SPHERE METHOD)5
- 2.2 PHOTOMETRIC AND ELECTRICAL MEASUREMENT (GONIOPHOTOMETER METHOD)5
- 2.3 DEVIATION FROM STANDARD OPERATING PROCEDURE5

3 – SUMMARY OF TEST RESULT6

4 – SPECTRAL FLUX PLOTS7

5 – EUT PHOTOS.....8

6 – LUMINOUS INTENSITY DISTRIBUTION TEST PLOTS (CIE CHROMATICITY).....9



1 - GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

Applicant	:	Hengdian Group Tospo Lighting Co.,Ltd
Product Name	:	LED
Model No	:	694795
Brand	:	TOSPO
Nominal Operation Voltage	:	AC 120V
Nominal Power	:	4.7W
Nominal CCT	:	2700K
Nominal CRI	:	80
Nominal Lumen Output	:	300Lumens
Nominal Life Time	:	25000 Hours
Number of hours operated prior to measurement for new sample	:	0 Hours
Stabilization Time	:	1.0 hours
Total operating time for measurement include stabilization time	:	2.5 hours
		<input checked="" type="checkbox"/> Standard <input type="checkbox"/> Non Standard
Nominal Shape of Bulb(Designation)	:	<input type="checkbox"/> Omnidirectional A, BT, P, PS, S, T <input checked="" type="checkbox"/> Decorative B, BA, C, CA, DC, F, G <input type="checkbox"/> Directional BR, ER, K, MR, PAR, R
Date of Receiving Sample	:	Jan 22, 2015
Date of Measurement performed	:	Jan 22, 2015 to jan 28, 2015
Measurement quantities measured	:	1 pcs
Orientation During Testing	:	Base Up
Test Requested	:	1. Electrical and Photometric Test 2. Luminous Intensity Distribution Test

1.2 Objective

The following test report is prepared on behalf of Hengdian Group Tospo Lighting Co.,Ltd in accordance with IESNA LM-79-08, used the following American National Standards or illumination Engineering Society of North America test guides:

- ANSI C78.377-2008: Specifications for the Chromaticity of Solid State Lighting Products;
- ANSI C79.1– 2002: American National Standard for Electric Lamps – Nomenclature for Glass Bulbs Intended for Use with Electric Lamps;
- ANSI C78.20 – 2003: American National Standard for Electric Lamps – A, G, PS, and Similar Shapes with E26 Medium Screw Bases;
- ANSI C78.21 – 2011: American National Standard for Incandescent lamps – PAR and R Shapes;
- ANSI C78.24 – 2001: American National Standard for Electric Lamps – Two-inch (51 mm); Integral-reflector Lamps with Front Covers and GU5.3 or GX 5.3 Bases;
- ANSI/IEC C81.61-2003: American National Standard for Electric Lamp Bases;
- ANSI/IEEE C62.41 – 1991 (01-May-1991): Surge Voltages in Low-Voltage AC Power Circuits, Recommended Practice for;
- CIE Publication No. 13.3 – 1995: Method of Measuring and Specifying Color Rendering of Light Sources;
- CIE Publication No. 18.2 – 1983: The Basis of Physical Photometry;
- IESNA LM-16-1993: Practical Guide to Colorimetry of Light Sources;
- IESNA LM-28-89: Guide for the Selection, Care, and Use of Electrical Instruments in the Photometric Laboratory;

IESNA LM-79-08 Electrical and Photometric Measurement of Solid State Lighting Products

UL 1993 – 1999: Standard for Self-Ballasted Lamps and Lamp Adapters;

UL 8750 – 2009: Light Emitting Diode (LED) Equipment for Use in Lighting Products.

1.3 Test Facility Description

The Energy Efficiency Lab used by BEST to collect energy efficiency measurement data is located in 1st Floor, 1st Building, Weitai Industrial Park, Yingrenshi, Shiyan, Baoan, Shenzhen, China. BEST Test Service Shenzhen Co., Ltd is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (Lab Code 200770-0). BEST Test Service Shenzhen Co., Ltd is also an ELI accredited lab for lighting products (ELI Certificate No. ELI-L04-2010) and UL accredited lab for lighting products.

1.4 Test Equipment List

Apparatus List	Device	Cal. Date	Cal Due Date
1	Integral Sphere+ Spectrophotometer System	Mar 10, 2015	Mar 09, 2016
2	Digital Power Meter	Oct 18, 2014	Oct 17, 2015
3	Goniophotometer+ Spectrophotometer System	Nov 20, 2014	Nov 19, 2015
4	Standard Light Source	Sep 17, 2014	Sep 16, 2015
5	Standard Light Source	Sep 17, 2014	Sep 16, 2015
6	Digital Storage Oscilloscope	Oct 18, 2014	Oct 17, 2015
7	Ultra Compact Simulator	Oct 20, 2014	Oct 19, 2015
8	Temperature Chamber	Oct 20, 2014	Oct 19, 2015
9	Digital Caliper	Nov 20, 2014	Nov 19, 2015
10	Digital CC&CV DC Power Supply(30V 5A)	N/A	N/A
11	5 1/2 Digital Multimeter	Oct 18, 2014	Oct 17, 2015
12	Digital CC&CV DC Power Supply(120V 10A)	N/A	N/A
13	6 1/2 Digital Multimeter	Oct 18, 2014	Oct 17, 2015
14	Digital Multimeter	Oct 18, 2014	Oct 17, 2015
15	Temperature Recorder+Thermocouple	Nov 20, 2014	Nov 19, 2015
16	Timer Controller	Nov 20, 2014	Nov 19, 2015

Statement of Traceability: BEST Test Service Shenzhen Co., Ltd. certifies that all calibration has been performed using suitable standards traceable to the NIM China.

2 - Test Method

2.1 Photometric and Electrical Measurement (Integrated Sphere Method)

Total light output (luminous flux) for the $25^{\circ}\text{C} \pm 1^{\circ}\text{C}$ ambient temperature conditions is measured using a 1.6m 4II geometry integrating sphere. Temperature is measured at a position inside the sphere. Spectral radiant flux measurements are made using Lab sphere to the detector port of the integrating sphere. Each lamp is operated at rated voltage in its designated orientation. Each lamp should be stable before measurements are made. The determining method of stable is as follows:

Step 1 Take 3 measurements of the lamp light output at 15 minute interval (total time=30mintues.)This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 if the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable. Luminous flux, chromaticity coordinates, correlated color temperature and color rendering index for each lamp are calculated from the spectral radiant flux measurements taken at 2 nm intervals over the range 350 to 1050 nm. The calibration of the sphere photometer-spectrometer system is traceable to the NIST USA. Lamp efficacy (lumens per watts) for each lamp model is computed based on the revised luminous flux result. Electrical measurements including voltage, current, power and power factor are measured using the digital power Meter.

The total uncertainty of the light output measurements is estimated, at the 95% confidence level, not to exceed $\pm 1.12\%$ over the wavelength range 350-1050 nm.

2.2 Photometric and Electrical Measurement (GonioPhotometer Method)

A Goniometer was used to measure the intensity (candelas) at each angle of distribution for each sample; the photometric distance is 24m. Ambient temperature was measured equal to the height of the sample mounted on the Goniometer equipment. Each sample was operated at input rated voltage in its designated orientation. Each sample was allowed to be stable before measurement was made. Electrical measurements including voltage, current, power and power factor were measured using the Power Analyzer

Before each measurement, the method below should be used to determine the lamp is stable or not.

Step 1 Take 3 measurements of the lamp intensity at 15 minute interval (total time=30mintues.)This time period is in addition to the recommended pre-burning time.

Step 2 Calculate the percent difference between the maximum measured value and the minimum measured value for the three consecutive measurements.

Step 3 if the value calculated in Step 2 does not exceed 0.5 percent, the lamp is considered stable.

Some graphics were created with Photometric Plus software.


2.3 Deviation from standard operating procedure

None.

3 – Summary of Test Result

	Item	Test Result		Accreditation
Required Fields	Lumen Output (Lumens)	346.92		NVLAP/EPA
	Luminous Efficacy (lm/w)	77.58		NVLAP/EPA
	Correlated Color Temperature (CCT)	2712		NVLAP/EPA
	Color Rendering Index- CRI	81.8		NVLAP/EPA
	Input Power (W)	4.47		NVLAP/EPA
Optional Fields	Power Type	<input checked="" type="checkbox"/> AC	<input type="checkbox"/> DC	/
	Input Voltage (V)	120.0		NVLAP/EPA
	Input Current (A)	0.0451		NVLAP/EPA
	Power Factor	0.8257		NVLAP/EPA
	x(CIE 1931)	0.4620		NVLAP/EPA
	y(CIE 1931)	0.4160		NVLAP/EPA
	u' (CIE 1976)	0.2615		NVLAP/EPA
	v' (CIE 1976)	0.5297		NVLAP/EPA
	Duv(CIE 1976)	0.0018		NVLAP/EPA
	R9	7		NVLAP/EPA
	Beam Angle: (Degree)	97.1		NVLAP/EPA
	Center beam candlepower: (cd)	111		NVLAP/EPA
	Zonal lumen density (0-60°):	60.1%		NVLAP/EPA
	Zonal lumen density (60-90°):	18.6%		NVLAP/EPA
	Zonal lumen density (90-120°):	13.7%		NVLAP/EPA
Zonal lumen density (120-180°):	7.6%		NVLAP/EPA	

4 – Spectral Flux Plots




5 – EUT Photos



6 – Luminous Intensity Distribution Test Plots (CIE Chromaticity)

LAMP PHOTOMETRIC REPORT

Electrical: Voltage:120.0V Current:0.0451A Power:4.472W Factor:0.8257		
MODEL: 694795		
POWER: 4.7W	VOLTAGE: 120.0V	WORKING VOLTAGE: 120.0V
MANUFACTURER: TOSPO		Eff.: 77.58 lm/W



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	106.1	105.6	105.3	104.0	106.3	104.9	104.7	104.3	0- 10	9.532	9.532	2.75
20	109.0	110.7	104.2	101.0	108.1	106.3	106.2	107.5	10- 20	30.49	40.02	11.5
30	99.34	92.71	89.85	83.34	92.38	88.82	93.04	91.53	20- 30	45.98	86.00	24.8
40	69.64	66.94	63.98	60.17	64.47	62.63	66.77	67.02	30- 40	49.08	135.1	38.9
50	45.53	43.75	42.59	41.09	42.31	41.39	44.02	44.76	40- 50	41.03	176.1	50.8
60	31.34	30.67	30.38	28.64	28.20	28.46	30.24	31.01	50- 60	32.28	208.4	60.1
70	23.44	23.73	22.57	21.31	20.79	21.18	22.13	23.39	60- 70	25.53	233.9	67.4
80	18.82	19.34	18.34	17.36	16.86	17.10	17.43	18.92	70- 80	21.12	255.0	73.5
90	15.52	15.83	15.60	15.46	15.40	15.43	15.22	15.86	80- 90	18.12	273.2	78.7
100	15.06	15.24	15.24	15.14	15.06	15.17	15.28	15.50	90-100	16.79	289.9	83.6
110	14.76	14.83	14.88	14.83	14.87	15.03	15.20	15.20	100-110	15.98	305.9	88.2
120	14.51	14.57	14.15	14.32	14.40	14.64	14.93	15.22	110-120	14.74	320.7	92.4
130	13.11	13.03	12.80	12.36	12.15	12.16	12.81	13.38	120-130	12.54	333.2	96
140	10.23	10.20	10.19	8.725	8.730	8.731	9.882	10.49	130-140	8.717	341.9	98.6
150	4.960	4.594	3.209	1.609	1.445	2.200	3.187	4.486	140-150	4.247	346.2	99.8
160	0.7236	0.6953	0.5920	0.4463	0.4197	0.4645	0.5395	0.6611	150-160	0.6622	346.8	100
170	0	0	0	0	0	0	0	0	160-170	0.0841	346.9	100
180	0	0	0	0	0	0	0	0	170-180	0.0000	346.9	100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.6DEG
 Operators:David

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.287
 Humidity:67.1%
 Test Distance:2.455m [K=1.0000]

LUMINOUS DISTRIBUTION INTENSITY DATA

Electrical: Voltage:120.0V Current:0.0451A Power:4.472W Factor:0.8257		
MODEL: 694795		
POWER: 4.7W	VOLTAGE: 120.0V	WORKING VOLTAGE: 120.0V
MANUFACTURER: TOSPO		Eff.: 77.58 lm/W

Table--1

UNIT: cd

C (DEG) \ γ (DEG)	0	23	45	68	90	113	135	158	180	203	225	248	270	293	315	338			
0	91.4	91.9	92.4	92.9	93.3	93.7	94.2	94.7	91.4	91.9	92.4	92.9	93.3	93.7	94.2	94.7			
5	94.7	95.3	95.9	96.2	96.6	97.7	98.9	99.5	97.3	97.4	97.5	97.4	97.1	96.8	96.5	96.9			
10	106	106	106	105	105	104	104	105	106	106	105	104	105	105	104	105			
15	113	112	111	108	106	105	106	106	109	108	109	109	108	109	109	109			
20	109	110	111	108	104	101	101	102	108	108	106	106	106	105	108	108			
25	107	107	102	99.7	99.9	96.0	92.3	93.2	102	102	97.6	97.6	102	104	101	99.9			
30	99.3	99.1	92.7	90.0	89.9	86.0	83.3	84.5	92.4	92.7	88.8	89.7	93.0	95.5	91.5	91.0			
35	85.9	85.2	81.0	77.9	77.3	74.3	71.9	72.9	78.7	79.6	75.8	77.5	80.4	82.6	80.5	80.5			
40	69.6	69.6	66.9	64.3	64.0	61.8	60.2	60.7	64.5	64.8	62.6	64.0	66.8	68.0	67.0	67.3			
45	56.0	56.0	53.8	51.9	52.1	50.5	49.4	49.8	52.6	52.7	50.6	51.5	53.7	55.1	54.5	55.2			
50	45.5	45.5	43.7	42.5	42.6	41.7	41.1	41.1	42.3	42.5	41.4	42.3	44.0	45.0	44.8	45.7			
55	37.9	37.7	36.4	35.3	35.6	34.8	34.3	34.2	34.4	34.6	34.5	35.4	36.7	37.5	37.3	38.3			
60	31.3	31.4	30.7	30.0	30.4	29.1	28.6	28.4	28.2	28.4	28.5	29.0	30.2	31.3	31.0	31.6			
65	26.7	26.9	26.8	26.4	26.0	25.1	24.4	24.2	24.0	24.3	24.3	24.7	25.5	26.5	26.7	27.3			
70	23.4	23.6	23.7	23.1	22.6	21.8	21.3	21.2	20.8	21.0	21.2	21.4	22.1	22.8	23.4	24.1			
75	20.9	20.9	21.2	20.8	20.1	19.4	19.1	18.9	18.5	18.6	18.9	19.0	19.5	20.1	20.9	21.4			
80	18.8	18.8	19.3	19.1	18.3	17.6	17.4	17.2	16.9	16.8	17.1	17.1	17.4	18.1	18.9	19.2			
85	17.0	17.0	17.5	17.5	16.8	16.3	16.1	16.0	15.7	15.6	15.8	15.8	16.0	16.5	17.2	17.5			
90	15.5	15.5	15.8	16.1	15.6	15.4	15.5	15.6	15.4	15.3	15.4	15.3	15.2	15.5	15.9	16.1			
95	15.2	15.1	15.4	15.6	15.4	15.2	15.3	15.4	15.3	15.3	15.4	15.3	15.2	15.5	15.7	15.7			
100	15.1	14.9	15.2	15.4	15.2	15.2	15.1	15.2	15.1	15.1	15.2	15.2	15.3	15.4	15.5	15.4			
105	14.9	14.8	15.0	15.2	15.2	15.2	15.1	15.1	14.9	15.0	15.0	15.1	15.2	15.3	15.3	15.3			
110	14.8	14.7	14.8	15.0	14.9	14.9	14.8	15.0	14.9	15.0	15.0	15.1	15.2	15.3	15.2	15.1			
115	14.7	14.6	14.7	14.8	14.5	14.7	14.7	14.9	14.7	14.8	14.9	15.1	15.2	15.3	15.2	15.1			
120	14.5	14.4	14.6	14.6	14.1	14.3	14.3	14.6	14.4	14.5	14.6	14.7	14.9	15.2	15.2	14.9			
125	14.2	14.0	14.1	14.1	13.8	13.8	13.7	14.0	13.8	13.9	14.0	14.0	14.3	14.7	14.9	14.7			
130	13.1	13.0	13.0	13.0	12.8	12.5	12.4	12.4	12.1	12.1	12.2	12.5	12.8	13.2	13.4	13.4			
135	11.5	11.3	11.3	11.4	11.3	10.9	10.9	10.9	10.8	10.6	10.7	11.0	11.3	11.6	11.7	11.8			
140	10.2	10.1	10.2	10.4	10.2	9.50	8.72	8.58	8.73	8.46	8.73	9.09	9.88	10.5	10.5	10.5			
145	7.84	7.90	7.83	7.58	6.88	6.38	5.76	5.06	5.18	5.19	5.60	6.00	6.76	7.51	7.96	8.01			
150	4.96	4.80	4.59	3.98	3.21	2.33	1.61	1.43	1.44	1.78	2.20	2.63	3.19	3.80	4.49	4.96			
155	1.60	1.53	1.32	1.11	0.99	0.86	0.78	0.76	0.75	0.78	0.82	0.87	0.97	1.20	1.41	1.60			
160	0.72	0.72	0.70	0.65	0.59	0.51	0.45	0.42	0.42	0.43	0.46	0.49	0.54	0.60	0.66	0.72			
165	0.39	0.37	0.37	0.34	0.29	0.23	0.18	0.15	0.15	0.16	0.18	0.21	0.25	0.29	0.34	0.38			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.6DEG
 Operators:David

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.287
 Humidity:67.1%
 Test Distance:2.455m [K=1.0000]