



Item#: **91063**
LED A19 LAMP
 GENERAL PURPOSE REPLACEMENT

The Superior Life® lamps are an efficient way to light sockets once reserved for traditional lamps. They consume less energy, thereby significantly reducing operating costs. The superior life hours of this lamp make it ideal for hard to reach places, reducing maintenance.


FEATURES

- Lightweight and easy installation
- Consume up to 80% less energy
- Long lasting light compared to alternative lights

APPLICATION

A replacement for traditional light bulbs around the home and other commercial needs.

LIGHT DISTRIBUTION CURVE



ELECTRICAL

Wattage	9.5W
Voltage	120V
Current	95mA
Power Factor	0.9

LIGHTING PERFORMANCE

Lumens	800
Lumens Per Watt (Lm/W)	84
Color Temperature (CCT)	3000K
Color Rendering (CRI)	83
Beam Angle	230°

Dimmable Lighting Control *Dimmable*
 see compatibility report

ENVIRONMENT

Operating Temperature	-4° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	N/A
Suitable Fixture Type	Open

LIFESPAN

Average Life (Hours)	25,000
Warranty (Years)	3

COMPONENTS

LED Light Source	Smalite
------------------	---------

CONSTRUCTION

Housing	Aluminum / Plastic
Base / Power Supply	E26 - Medium
Finish	White

QUALIFICATIONS



Visit www.energystar.gov to confirm qualification. • Published lumens on LED products are approximate and may vary slightly.

PERFORMANCE DATA

PACKAGING

Item#: **91063**
LED A19 LAMP




DIMENSIONS (Inches)

Length (MOL)	4.4"
Width/Diameter (MOD)	2.4"
Weight (Lbs)	--

Line drawings may not be to scale and are for general reference only.

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Dimmer Compatibility	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	48	10811768029113	15.9" x 11.1" x 10.9"	5.3
Individual Box	1	811768029116	2.5" x 2.5" x 4.7"	0.1
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	CASE
91063	LED 9.5A19/OMNI/30K/DIMMABLE - SUPERIOR LIFE® ENERGY STAR ®	48

PERFORMANCE DATA

PACKAGING