



# Item#: 91194

INTERNAL DRIVER LAMP-STYLE RETROFIT KITS (UL TYPE B)

# **FEATURES**

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

# SINGLE ENDED DIRECT WIRE

- · No ballast required, lamp runs off main
- Exceptional efficacy
- \*Non-shunted sockets required, see install instructions for further details. Not for use with emergency fixtures.



	ΓRI	

Wattage	17W
Voltage	120-277V
Current	146-66mA
Power Factor	0.9
Total Harmonic Distortion (THD)	20
LIGHTING PERFORMANCE	
Lumens	2200
Lumens Per Watt (LPW)	129
Color Temperature (CCT)	4000K

Lumens rei wall (LPW)	129	
Color Temperature (CCT)	4000K	
Color Rendering (CRI)	80	
R9 (Red Value)		
R13 (Skin Tones)		
Beam Angle	220°	
Light Distribution	Type II, Very Short	
Dimmable Lighting Control	Only with Lutron, type NTELV-600, DVELV-300P or CTELV-303P on 120V	

# **ENVIRONMENT**

Operating Temperature	-13° ~ 104°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	

#### LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

### **COMPONENTS**

LED Light Source	SMD 2835
------------------	----------

# **CONSTRUCTION**

Housing Glass / Plastic End	
Lens	Frosted
Base / Power Supply	G13 - Medium Bi Pin

# **QUALIFICATIONS**









Visit www.designlights.org/search to confirm qualification. - Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


# Item#: 91194 LED DIRECT WIRE LINEAR T8



# **DIMENSIONS** (Inches)

Length (MOL)	48"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	

# SUPPORTING DOCUMENTS (Grey = not available at this time.) Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768021100	49.7" x 7.5" x 6.5"	11.6
Individual Box	1	811768021103		0.46
Country of Origin	China			
HS Tariff	8539.50.0050			

# **ORDERING**

ITEM#	DESCRIPTION	CASE
91194	LED 4FT 17WT8/40K/TYPE B/SE - <b>CEE/DLC</b> °	25

#### **ADDITIONAL INFORMATION:**

Family Item(s): 91193/3500K - 91195/5000K

• PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.