



91200
PAR20 SPOT CMH
CERAMIC METAL HALIDE


FEATURES

- Excellent color rendering
- Constant color over the life of the lamp
- Uniform lamp to lamp color
- Ultra-efficient energy usage


APPLICATION

Used in industrial, retail, outdoor, display, and down lighting.

PRODUCT DETAILS

ELECTRICAL	
Wattage	39W
Voltage	120V
ANSI Code	M130/O
LIGHTING PERFORMANCE	
Lumens	2150
Lumens Per Watt (Lm/W)	55
Color Temperature (CCT)	3000K
Color Rendering (CRI)	82
Beam Angle	10°
Dimmable Lighting Control	
LIFESPAN	
Average Life (Hours)	9,000
Warranty (Years)	1
ENVIRONMENT	
Operating Temperature	-30°C ~ 55°C
Fixture Type	Open
CERTIFICATIONS	
Ⓢ EISA Compliant (Meets US Min. Efficiency standards)	Yes


CONSTRUCTION	
Housing	Glass
Base / Power Supply	E26-Medium
Finish	Silver
Mercury Content (Hg)	3mg
PACKAGING	
Master Carton	72pc / 10811768022626
Inner Carton	6pc / 20811768022623
Individual Box	811768022629
Country of Origin	China
HS Tariff	8539.32.0020
DIMENSIONS	
Dimensions (Inches)	3.5"(L) x 2.5"(DIA)



ORDERING

ITEM#	DESCRIPTION	CASE
91200	CMH39PAR20/SPOT/830 - SUPERIOR LIFE®	72

Note: Must only be operated on a thermally protected ballast.

 This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

Published lumens on products are approximate and may vary slightly.