





Item#: 91203 CMH PAR30 FL00D CERAMIC METAL HALIDE

FEATURES

- · Excellent color rendering
- · Constant color over the life of the lamp
- Uniform lamp to lamp color
- Ultra-efficient energy usage

APPLICATION

Used in industrial, retail, outdoor, display and down lighting.

*Must be operated on a thermally protected ballast.

Wattage	39W	
Voltage	120V	
ANSI Code	M130/0	
LIGHTING PERFORMANCE		
Lumens	2300	
Lumens Per Watt (Lm/W)	59	
Color Temperature (CCT)	3000K	
Color Rendering (CRI)	82	
Beam Angle	30°	
Dimmable Lighting Control	Les controles.	

ENVIRONMENT

Operating lemperature	-22 ~ I31°F
Fixture Type	0pen
LIFESPAN	

LIFE SPAN

Average Life (Hours)	9,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass		
Base / Power Supply	E26 - Medium		
Finish	Silver		
Mercury Content ⁽¹⁹⁾	3.2mg		

QUALIFICATIONS

© EISA Compliant (Meets US Min. Efficiency standards)

Yes



Published lumens are approximate and may vary slightly. Specifications are subject to change without notice. This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

Item#: **91203 CMH PAR30 FL00D**






DIMENSIONS (Inches)

Length (MOL)	4.7"
Width/Diameter (MOD)	3.7"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS

Donador at Object	1/1514/
Product Sheet	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	36	10811768021391	19.7" x 15.2" x 18.5"	25.4
Inner Carton	6	20811768021398		
Individual Box	1	811768021394		0.7
Country of Origin	China			
HS Tariff	8539.32.0020			

ORDERING

ITEM#	DESCRIPTION	CASE
91203	CMH39PAR30/FL/830 · M130/0 - SUPERIOR LIFE®	36

ADDITIONAL INFORMATION:

- Operate on a thermally protected ballasts only.