



Item#: **91204**
CMH PAR30 FLOOD
CERAMIC METAL HALIDE

FEATURES

- Excellent color rendering
- Constant color over the life of the lamp
- Uniform lamp to lamp color
- Ultra-efficient energy usage

APPLICATION


Used in industrial, retail, outdoor, display and down lighting.

**Must be operated on a thermally protected ballast.*

ELECTRICAL

Wattage	39W
Voltage	120V
ANSI Code	M130/0

LIGHTING PERFORMANCE

Lumens	2400
Lumens Per Watt (LPW)	62
Color Temperature (CCT)	4200K
Color Rendering (CRI)	82
Beam Angle	30°
Dimmable Lighting Control	

ENVIRONMENT

Operating Temperature	-22 ~ 131°F
Fixture Type	Open

LIFESPAN

Average Life (Hours)	9,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass
Base / Power Supply	E26 - Medium
Finish	Silver
Mercury Content ^(Hg)	3.2mg

QUALIFICATIONS

ⓔ EISA Compliant (Meets US Min. Efficiency standards)	Yes
---	-----

TCLP
COMPLIANT

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.


Item#: **91204**
CMH PAR30 FLOOD



ITEM INFORMATION

DIMENSIONS (Inches)

Length (MOL)	4.7"
Width/Diameter (MOD)	3.7"
Net Weight (Lbs)	--



SUPPORTING DOCUMENTS

Product Sheet	VIEW
---------------	------

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	36	10811768027799	19.7" x 15.2" x 18.5"	25.4
Individual Box	1	811768027792	--	0.7
Country of Origin	China			
HS Tariff	8539.32.0020			

ORDERING

ITEM#	DESCRIPTION	CASE
91204	CMH39PAR30/FL/942 - M130/0	36

ADDITIONAL INFORMATION:

- Operate on a thermally protected ballasts only.