



Item#: **91205**
CMH PAR30 SPOT
 CERAMIC METAL HALIDE

FEATURES

- Excellent color rendering
- Constant color over the life of the lamp
- Uniform lamp to lamp color
- Ultra-efficient energy usage

APPLICATION

Used in industrial, retail, outdoor, display and down lighting.

**Must be operated on a thermally protected ballast.*

PERFORMANCE DATA

ELECTRICAL

Wattage	39W
Voltage	120V
ANSI Code	M130/0

LIGHTING PERFORMANCE

Lumens	2300
Lumens Per Watt (Lm/W)	59
Color Temperature (CCT)	3000K
Color Rendering (CRI)	82
Beam Angle	10°
Dimmable Lighting Control	

ENVIRONMENT

Operating Temperature	-22 ~ 131°F
Fixture Type	Open

LIFESPAN

Average Life (Hours)	9,000
Warranty (Years)	1

CONSTRUCTION

Housing	Glass
Base / Power Supply	E26 - Medium
Finish	Silver
Mercury Content (Hg)	3.2mg

QUALIFICATIONS

Ⓔ EISA Compliant (Meets US Min. Efficiency standards)	Yes
---	-----

TCLP
 COMPLIANT

Published lumens are approximate and may vary slightly. • Specifications are subject to change without notice. • This lamp contains mercury. For proper lamp disposal contact your local municipal solid waste agency directly, call 888-537-4874 or visit lamprecycle.org for state-specific lamp recycling options.

Item#: **91205**
CMH PAR30 SPOT




DIMENSIONS (Inches)

Length (MOL)	4.7"
Width/Diameter (MOD)	3.7"
Net Weight (Lbs)	--

SUPPORTING DOCUMENTS

Product Sheet	VIEW
---------------	------



PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	36	10811768023067	19.7" x 15.2" x 18.5"	25.4
Inner Carton	6	20811768023064	--	--
Individual Box	1	811768023060	--	0.7
Country of Origin	China			
HS Tariff	8539.32.0020			

ORDERING

ITEM#	DESCRIPTION	CASE
91205	CMH39PAR30/SP/830 - M130/0 - SUPERIOR LIFE®	36

ADDITIONAL INFORMATION:

- Operate on a thermally protected ballasts only.