



Item#: **91238**
LED A15 LAMP
 GENERAL PURPOSE REPLACEMENT

FEATURES

- Lightweight and easy installation
- Consume up to 80% less energy
- Long lasting light compared to alternative lights

APPLICATION

A replacement for traditional light bulbs around the home and other commercial needs.

ELECTRICAL

Wattage	4.5W
Voltage	120V
Current	68mA
Power Factor	0.7
Total Harmonic Distortion (THD)	--

LIGHTING PERFORMANCE

Lumens	300
Lumens Per Watt (Lm/W)	67
Color Temperature (CCT)	5000K
Color Rendering (CRI)	80
R9 (Red Value)	--
R13 (Skin Tones)	--
Beam Angle	150°
Dimmable Lighting Control	

ENVIRONMENT

Starting Temperature	-4 ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	N/A
Suitable Fixture Type	Open

LIFESPAN

Average Life (Hours)	15,000
Warranty (Years)	3

COMPONENTS

LED Light Source	--
------------------	----

CONSTRUCTION

Housing	Aluminum / PC
Base / Power Supply	E26 - Medium
Finish	White

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly.

PERFORMANCE DATA

PACKAGING


Item#: **91238**
LED A15 LAMP



DIMENSIONS (Inches)

Length (MOL)	3.3"
Width/Diameter (MOD)	1.8"
Weight (Lbs)	--

Line drawings may not be to scale and are for general reference only.



SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

PACKAGING

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	48	10811768029908	12.1"x8.3"x8.3"	--
Individual Box	1	811768029901	1.9"x1.9"x3.5"	--
Country of Origin	China			
HS Tariff	9405.40.6000			

ORDERING

ITEM#	DESCRIPTION	CASE
91238	LED 4.5WA15/50K - SUPERIOR LIFE®	48

ADDITIONAL INFORMATION:

Family Item: 91236/3000K · 91237/4000K

PERFORMANCE DATA

PACKAGING