



Item#: 91286 **LED DIRECT WIRE LINEAR T8 INTERNAL DRIVER LAMP-STYLE RETROFIT KITS** (UL TYPE B)

FEATURES

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

SINGLE ENDED DIRECT WIRE

- · No ballast required, lamp runs off main
- Exceptional efficacy
- ETL Sanitation Listed (NSF-2)
- *Non-shunted sockets required, see install instructions for further details. Not for use with emergency fixtures.

ELECTRICAL

Wattage	9W
Voltage	120-277V
Current	100mA
Power Factor	0.9
Total Harmonic Distortion (THD)	20
LIGHTING PERFORMANCE	
Lumens	1200

Lumens Per Watt (LPW)	133		
Color Temperature (CCT)	4000K		
Color Rendering (CRI)	82		
R9 (Red Value)	2		
R13 (Skin Tones)	83		
Beam Angle	180°		
Light Distribution	Type VS		
DIIC Deting (D. 18 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1 1.1	4 Lamp	B2 - U3 - G1	
BUG Rating (Backlight, Uplight, and Glare)	6 Lamp	B2 - U3 - G2	

ENVIRONMENT

Operating Temperature	-13° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Enclosed

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

LED Light Source	Samsung

CONSTRUCTION

Housing	Glass / Plastic End Caps		
Lens	Frosted		
Base / Power Supply	G13 - Medium Bi Pin		

QUALIFICATIONS







RoHS

Visit www.designlights.org/search to confirm qualification. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


Item#: 91286 LED DIRECT WIRE LINEAR T8



DIMENSIONS (Inches)

Length (MOL)	24"
Width/Diameter (MOD)	1"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)		
Product Sheet	VIEW	
Install Instructions	VIEW	
IES Download from Web Item	VIEW	
LM79	VIEW	
LM80	VIEW	



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768025146	26.2" x 7.3" x 7.3"	9.9
Individual Box	1	811768025146		0.4
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
91286	LED 2FT 9WT8/40K/TYPE B/SE - DLC °	25

ADDITIONAL INFORMATION:

Family Item(s): 91287/5000K

• PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.