



Item#: **91310 LED PLUG & GO[™] LINEAR T8** REPLACEMENT LAMPS (PLUG AND PLAY)

REPLACEMENT LAMPS (PLUG AND PLAY) (UL TYPE A)

FEATURES


Our T8 LED tube can work with the most popular electronic ballasts that are capable of replacing your existing fluorescent T8 lamps without any additional wiring. It provides exceptional LED lighting with reduced energy and maintenance costs.

PLUG & GO[™] - WORKS WITH EXISTING ELECTRONIC BALLAST*

- Exceptional efficacy
- No flickering
- ETL Sanitation Listed (NSF-2)

*Suitable for dimming and emergency ballasts.

LIGHT DISTRIBUTION CURVE



ELECTRICAL	LAMP	DLC [®] System Power		
Wattage	15W	18W		
Voltage	120-	277V		
Current	0.2	0.286A		
Power Factor	0	.9		
Total Harmonic Distortion (THD)	11	11.3		
LIGHTING PERFORMANCE				
Lumens	23	00		
Lumens Per Watt (Lm/W)	12	28		
Color Temperature (CCT)	40	4000K		
Color Rendering (CRI)	8	83		
R9 (Red Value)		1		
R13 (Skin Tones)	8	82		
Beam Angle	16	160°		
Light Distribution	Тур	Type VS		
BUG Rating (Backlight, Uplight, and Glare)	4 Lamp	B3 - U3 - G1		
	6 Lamp	B3 - U4 - G2		
Dimmable Lighting Control	Unless compatible	Unless compatible ballast is dimmable.		
ENVIRONMENT				
Operating Temperature	-4° ~	-4° ~ 113°F		
Suitable Location	DA	DAMP		
Ingress Protection Rating	IP	IP20		
Suitable Fixture Type	Encl	Enclosed		
LIFESPAN				
Average Life (Hours)	50,	50,000		
Warranty (Years)	-	5		
COMPONENTS				
LED Light Source	Everligi	Everlight 67-21S		
CONSTRUCTION				
Housing	Glass / Met	Glass / Metal End Caps		
Lens		Frosted		
Base / Power Supply	G13 - Med	G13 - Medium Bi Pin		

QUALIFICATIONS



Visit www.designlights.org/search to confirm qualification. · DLC lists the wattage of the system power. · Published lumens on LED products are approximate and may vary slightly. · Specifications are subject to change without notice.

Item#: **91310** LED PLUG & GO[™] LINEAR T8




DIMENSIONS (Inches)

Length (MOL)	48″
Width/Diameter (MOD)	1″
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)

Product Sheet	VIEW
Install Instructions	VIEW
Ballast Compatibility	VIEW
IES Download from Web Item	VIEW
Photometric 4 Lamp	VIEW
Photometric 6 Lamp	VIEW
LM79	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768026440	50.2" x 6.9" x 6.9"	15.6
Individual Box	1	811768026443		0.63
Country of Origin	China			
HS Tariff	8539.50.0050			

ORDERING

ITEM#	DESCRIPTION	CASE
91310	LED 4' 15WT8/40K/FR/PLUG & GO™/V5 - SUPERIOR LIFE° CEE/DLC °	25

ADDITIONAL INFORMATION:

Family Item(s): 91309/3500K