



Item#: 91413 **LED DUAL POWER LINEAR T8 INTERNAL DRIVER LAMP-STYLE RETROFIT KITS** (UL TYPE B)

### **FEATURES**

Our T8 LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

### SINGLE OR DOUBLE ENDED DIRECT WIRE

- No ballast required, lamp runs off main
- Dual wiring capabilities (single or double-ended)
- · Lamp works by any two pins on line voltage
- · Wide light emitting area
- Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets



Wattage	18.5W	
Voltage	120-277V	
Current	175mA	
Power Factor	0.9	
LIGHTING PERFORMANCE		
Lumens	2600	
Lumens Per Watt (Lm/W)	141	
Color Temperature (CCT)	6500K	
Color Rendering (CRI)	83	
Beam Angle	160°	
Light Distribution	Type VS	
Dimmable Lighting Control	OUT DOMAN SELL	
ENVIRONMENT		
Operating Temperature	-4° ~ 113°F	
Suitable Location	DAMP	
Ingress Protection Rating	IP20	
Suitable Fixture Type	Enclosed	
LIFESPAN		
Average Life (Hours)	50,000	
Warranty (Years)	5	

**LED Light Source** Everlight 67-21S

### CONSTRUCTION

•
Frosted / Safety Coated
G13 - Medium Bi Pin

### **QUALIFICATIONS**






Published lumens on LED products are approximate and may vary slightly.

# Item#: **91413**LED DUAL POWER LINEAR T8



### **DIMENSIONS** (Inches)

Length (MOL)	48"	
Width/Diameter (MOD)	1"	
Weight (Lbs)	0.7	



## SUPPORTING DOCUMENTS (Grey = not available at this time.)

Install Instructions	VIEW
LM80	VIEW

PACKAGING		UPC	<b>DIMENSIONS</b> (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25		50.2" x 7.3" x 7.3"	16.5
Individual Box	1			
Country of Origin	China			
HS Tariff	8539.52.0051			

### **ORDERING**

ITEM#	DESCRIPTION	CASE
91413	LED 4FT 18.5WT8/65K/TYPE B/DE/SAFETY COATED	25

### **ADDITIONAL INFORMATION:**

Safety Feature: Tube(s) will not light if power is still running through the ballast. Refer to the install instructions for proper installation.