

Item#: **91545**  
**LED TONE-SELECT™ CFL DIRECT WIRE**  
 MEDIUM BASE REPLACEMENT LAMP FOR CFL

**FEATURES**

- Adjustable color temperature for custom lighting application.
- Exceptional efficacy.
- Universal voltage using direct wire.
- Rotating base for precise positioning.

**- APPLICATION**

Replaces traditional CFL lamps frequently used in downlights and sconces.  
*\*Not suitable for use with emergency exits or lighting.*

PERFORMANCE DATA

**ELECTRICAL**

Wattage	6W
Voltage	120-277V
Current	55mA
Power Factor	--

**LIGHTING PERFORMANCE**

Lumens	550-625
Lumens Per Watt (Lm/W)	92-104
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	83
Beam Angle	120°
Light Distribution	Type II, Very Short
BUG Rating (Backlight, Uplight, and Glare)	B0 - U2 - G1
Dimmable Lighting Control	

**ENVIRONMENT**

Operating Temperature	-4° ~ 113°F
Suitable Location	<b>DAMP</b>
Ingress Protection Rating	IP20
Fixture Type	Enclosed

**LIFESPAN**

Average Life (Hours)	50,000
Warranty (Years)	<b>5</b>

**COMPONENTS**

LED Light Source	Samsung
------------------	---------

**CONSTRUCTION**

Housing	Aluminum / PC
Lens	Frosted
Base / Power Supply	Medium
Finish	White / Silver

**QUALIFICATIONS**



*Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.*


Item#: **91545**  
**LED TONE-SELECT™ CFL DIRECT WIRE**



ITEM INFORMATION

**DIMENSIONS** (Inches)

Length (MOL)	5.9"
Width/Diameter (MOD)	1.4"
Weight (Lbs)	--



**SUPPORTING DOCUMENTS** (Grey = not available at this time.)

Product Sheet	VIEW
IES Download from Web Item	VIEW
LM79	VIEW
LM80	VIEW

**PACKAGING**

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	50	10811768021612	17.7" x 8.9" x 6.7"	--
Inner Carton	10	20811768021619	--	--
Individual Box	1	811768021615	6.4" x 1.7" x 1.7"	--
Country of Origin	China			
HS Tariff	8539.50.0010			

**ORDERING**

ITEM#	DESCRIPTION	TITLE 20	CASE
91545	LED TONE-SELECT™ 6WT10/120°/FR/27/30/35/40/50K/MED/120-277V - SUPERIOR LIFE®	Yes	50

**ADDITIONAL INFORMATION:**

**CCT DIP SWITCH SETTINGS**

CCT	Switch 1	Switch 2	Switch 3
2700K	--	ON	--
3000K	ON	--	ON
3500K	--	ON	ON
4000K	ON	--	--
5000K	--	--	ON

TOP VIEW

