



Item#: **91838**  
**LED HYBRID LINEAR T5**  
DUAL MODE INTERNAL DRIVER  
(UL TYPE A AND TYPE B)

**FEATURES**

The LED T5 Linear Hybrid tubes provides exceptional lighting with reduced energy and maintenance costs. The hybrid tube works with or without a ballast, making it a top-of-the-line replacement for standard fluorescent lamps.

**PLUG & GO™ OR SINGLE / DOUBLE ENDED DIRECT WIRE**

Use with an instant start ballast as a direct replacement lamp or simple rewiring allows lamp to run directly off the main.

- Wide beam design
- Exceptional efficacy

<b>ELECTRICAL</b>	<b>LAMP</b>	<b>DLC® SYSTEM POWER</b>
Wattage	24W	27.5W
Voltage	120-277V	
Current	222mA	
Power Factor	0.9	
Total Harmonic Distortion (THD)	20	

<b>LIGHTING PERFORMANCE</b>		
Lumens	3300	
Lumens Per Watt (LPW)	120	
Color Temperature (CCT)	5000K	
Color Rendering (CRI)	80	
R9 (Red Value)	10	
Beam Angle	180°	
Light Distribution	Type VS	
BUG Rating (Backlight, Uplight, and Glare)	--	
Dimmable Lighting Control	See Install Instructions	

<b>ENVIRONMENT</b>		
Operating Temperature	-4° ~ 113°F	
Suitable Location	<b>DAMP</b>	
Ingress Protection Rating	IP20	
Suitable for Emergency Fixtures/Ballasts	No	

<b>LIFESPAN</b>		
Average Life (Hours)	50,000	
Warranty (Years)	<b>5</b>	

<b>COMPONENTS</b>		
LED Light Source	--	

<b>CONSTRUCTION</b>		
Housing	Glass / Plastic End Caps	
Lens	Frosted / Safety Coated	
Base / Power Supply	G5 - Mini Bi Pin	

**QUALIFICATIONS**



Visit [www.designlights.org/search](http://www.designlights.org/search) to confirm qualification. • DLC lists the wattage of the system power. • Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.


Item#: **91838**  
**LED HYBRID LINEAR T5**



ITEM INFORMATION

**DIMENSIONS** (Inches)

Length (MOL)	45.8"
Width/Diameter (MOD)	0.6"
Net Weight (Lbs)	--



**PACKAGING**

		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768029755	46.8" x 4.9" x 5.3"	--
Individual Item	--	811768029758	N/A	N/A
Country of Origin	China			
HS Tariff	--			

**ORDERING**

ITEM#	DESCRIPTION	CASE
91838	LED 4FT 24WT5/50K/TYPE A & B/SAFETY COATED - DLC®	25

**ADDITIONAL INFORMATION:**

- PQL Direct-Wire (UL Type B) Lamps are designed for use with PQL LED-Ready fixtures (follow lamp wiring instructions). When using any alternate-brand fixture, please review the specific PQL lamp installation guide wiring requirements first, to make sure the fixture is compatible before lamp installation.