



Item#: **91841 LED TONE-SELECT™ DUAL POWER LINEAR T5**

INTERNAL DRIVER LAMP-STYLE RETROFIT KITS (UL TYPE B)

FEATURES

Our LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

SINGLE OR DOUBLE ENDED DIRECT WIRE

- Adjustable color temperature (3 Settings)
- No ballast required, lamp runs off main
- Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets (Review install instructions for more details.).

ELECTRICAL

Wattage	16W
Voltage	120-277V
Current	140mA
Power Factor	0.9
Total Harmonic Distortion (THD)	20

LIGHTING PERFORMANCE

Lumens	2050 / 2100 / 2100
Lumens Per Watt (LPW)	130
Color Temperature (CCT)	3500K / 4000K / 5000K
Color Rendering (CRI)	83
R9 (Red Value)	
R13 (Skin Tones)	
Beam Angle	180°
BUG Rating (Backlight, Uplight, and Glare)	

ENVIRONMENT

Operating Temperature	-4° ~ 113°F
Suitable Location	DAMP
Ingress Protection Rating	IP20
Suitable Fixture Type	Open
Suitable for Emergency Fixtures	No
	

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5

COMPONENTS

Samsung

CONSTRUCTION

Housing Glass / Plastic End			
Lens	Safety Coated		
Base / Power Supply	G5 - Mini Bi Pin		

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: **91841 LED TONE-SELECT™ DUAL POWER LINEAR T5**



DIMENSIONS (Inches)

Length (MOL)	34"
Width/Diameter (MOD)	0.8"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.) Product Sheet Install Instructions VIEW LM79 VIEW LM80 VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	25	10811768027201		
Individual Box	1	811768027204		
Country of Origin	China			
HS Tariff	8539.52.0051			

ORDERING

ITEM#	DESCRIPTION	CASE
91841	LED 3FT TONE-SELECT™ 16WT5/35-40-50K/TYPE B/DE/SAFETY COATED	25

ADDITIONAL INFORMATION:

Safety Feature: Tube(s) will not light if power is still running through the ballast. Refer to the install instructions for proper installation.