



Item#: **91842 LED TONE-SELECT™ DUAL POWER LINEAR T5**

INTERNAL DRIVER LAMP-STYLE RETROFIT KITS (UL TYPE B)

FEATURES

Our LED tube lamp provides exceptional LED lighting with reduced energy and maintenance costs. The linear LED does not use a fluorescent ballast to work; instead they feature a built-in universal line voltage driver, making it a top of the line replacement for standard fluorescent lamps.

SINGLE OR DOUBLE ENDED DIRECT WIRE

- Adjustable color temperature (3 Settings)
- No ballast required, lamp runs off main
- Exceptional efficacy
- Suitable for both Shunted and Non-Shunted Sockets (Review install instructions for more details.).

ELECTRICAL

| Wattage | 25W |
|---------------------------------|----------|
| Voltage | 120-277V |
| Current | 215mA |
| Power Factor | 0.9 |
| Total Harmonic Distortion (THD) | 20 |
| | |

LIGHTING PERFORMANCE

| Lumens | 3400 / 3500 / 3500 | | |
|--|-----------------------|--|--|
| Lumens Per Watt (LPW) | 130 | | |
| Color Temperature (CCT) | 3500K / 4000K / 5000K | | |
| Color Rendering (CRI) | 83 | | |
| R9 (Red Value) | 17 | | |
| R13 (Skin Tones) | 88 | | |
| Beam Angle | 180° | | |
| BUG Rating (Backlight, Uplight, and Glare) | B1 - U3 - G2 | | |
| | · | | |

ENVIRONMENT

| -4° ~ 113°F |
|-------------|
| DAMP |
| IP20 |
| 0pen |
| No |
| |

LIFESPAN

| Average Life (Hours) | 50,000 |
|----------------------|--------|
| Warranty (Years) | 5 |

COMPONENTS

| LED Light Source | Samsung |
|------------------|------------|
| LLD LIGHT Source | Sallisully |

CONSTRUCTION

| Housing Glass / Plastic End Ca | |
|--------------------------------|------------------|
| Lens | Safety Coated |
| Base / Power Supply | G5 - Mini Bi Pin |

QUALIFICATIONS







Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: **91842**LED TONE-SELECT™ DUAL POWER LINEAR T5



DIMENSIONS (Inches)

| Length (MOL) | 45.8′ |
|----------------------|-------|
| Width/Diameter (MOD) | 0.8" |
| Net Weight (Lbs) | |

SUPPORTING DOCUMENTS (Grey = not available at this time.) Product Sheet VIEW Install Instructions VIEW IES Download from Web Item VIEW LM79 VIEW LM80 VIEW



| PACKAGING | | UPC | DIMENSIONS (LxWxH) | GROSS WEIGHT (Lbs) |
|-------------------|--------------|----------------|---------------------------|---------------------------|
| Master Carton | 25 | 10811768025139 | | |
| Individual Box | 1 | 811768025132 | | |
| Country of Origin | China | | | |
| HS Tariff | 8539.52.0051 | | | |

ORDERING

| ITEM# | DESCRIPTION | CASE |
|-------|---|------|
| 91842 | LED 4FT TONE-SELECT™ 25WT5/35-40-50K/TYPE B/DE/SAFETY COATED - DLC ° | 25 |

ADDITIONAL INFORMATION:

Safety Feature: Tube(s) will not light if power is still running through the ballast. Refer to the install instructions for proper installation.