



SELECTABLE  
COLOR  
TEMPERATURE

Item#: **91854**  
**LED TONE-SELECT™ BR30 LAMP**  
REFLECTOR (FLOOD/SPOT)

**FEATURES**

- Adjustable color temperature for custom lighting application.
- Superior lighting performance
- Energy efficient
- Innovative and durable design that resembles traditional lighting
- UL 94 V-0: Shatter-resistant, flame-resistant polycarbonate lens
- Ideal replacement for 65W traditional lamps

**APPLICATION**

Indoor residential and commercial spaces, track lighting and recessed downlights.

**ELECTRICAL**

Wattage	8.5W
Voltage	120V
Current	90mA
Power Factor	0.7

**LIGHTING PERFORMANCE**

Lumens	700
Lumens Per Watt (LPW)	82
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	90
Beam Angle	110°
Dimmable Lighting Control	<i>Dimmable</i> see compatibility report

**ENVIRONMENT**

Operating Temperature	-4° ~ 104°F
Suitable Location	<b>DAMP</b>
Ingress Protection Rating	IP20
Suitable Fixture Type	Open

**LIFESPAN**

Average Life (Hours)	25,000
Warranty (Years)	<b>3</b>

**COMPONENTS**

LED Light Source	Lumileds
------------------	----------

**CONSTRUCTION**

Housing	Aluminum / PC
Base / Power Supply	E26 - Medium
Finish	White

**QUALIFICATIONS**



*Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.*


Item#: **91854**  
**LED TONE-SELECT™ BR30 LAMP**



ITEM INFORMATION

**DIMENSIONS** (Inches)

Length (MOL)	5"
Width/Diameter (MOD)	3.7"
Weight (Lbs)	0.06



**SUPPORTING DOCUMENTS** (Grey = not available at this time.)

Product Sheet	VIEW
Dimmer Compatibility	VIEW
LM80	VIEW

PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	24	10811768021452	15.5" x 11.7" x 10.6"	3.9
Individual Box	1	811768021455	3.8" x 3.8" x 5"	0.16
Country of Origin	China			
HS Tariff	8539.50.0010			

**ORDERING**

ITEM#	DESCRIPTION	TITLE 20	TITLE 24	CASE
91854	LED TONE-SELECT™ 8.5WBR30/27-30-35-40-50K/110°/DIMM	--	No	24

**ADDITIONAL INFORMATION:**

- Using the CCT slider on the side of lamp to select the desired color temperature.