



SELECTABLE  
COLOR  
TEMPERATURE

Item#: **91862**  
**LED TONE-SELECT™ A19 LAMP**  
GENERAL PURPOSE REPLACEMENT

**FEATURES**

- Adjustable color temperature for custom lighting application.
- Superior lighting performance
- Energy efficient
- Long lasting light compared to alternative lights
- UL 94 V-0: Shatter-resistant, flame-resistant polycarbonate lens
- Ideal replacement for 60W traditional lamps

**APPLICATION**

A replacement for traditional light bulbs around the home and other commercial needs.

**ELECTRICAL**

Wattage	9W
Voltage	120V
Current	115mA
Power Factor	0.6

**LIGHTING PERFORMANCE**

Lumens	800
Lumens Per Watt (LPW)	89
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	80
Beam Angle	220°
Dimmable Lighting Control	<i>Dimmable</i> see compatibility report

**ENVIRONMENT**

Operating Temperature	-4° ~ 104°F
Suitable Location	<b>DAMP</b>
Ingress Protection Rating	IP20
Suitable Fixture Type	Open

**LIFESPAN**

Average Life (Hours)	25,000
Warranty (Years)	<b>3</b>

**COMPONENTS**

LED Light Source	Lumileds
------------------	----------

**CONSTRUCTION**

Housing	Aluminum / PC
Base / Power Supply	GU24
Finish	White

**QUALIFICATIONS**



*Published lumens on LED products are approximate and may vary slightly. • Specifications are subject to change without notice.*

Item#: **91862**  
**LED TONE-SELECT™ A19 LAMP**




ITEM INFORMATION

**DIMENSIONS** (Inches)

Length (MOL)	4.2"
Width/Diameter (MOD)	2.4"
Weight (Lbs)	0.06

**SUPPORTING DOCUMENTS** (Grey = not available at this time.)

Product Sheet	VIEW
Dimmer Compatibility	VIEW
LM80	VIEW



PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	96	10811768023616	19.7" x 14.8" x 9.1"	8.1
Individual Box	1	811768023619	2.4" x 2.4" x 4.3"	0.08
Country of Origin	China			
HS Tariff	8539.50.0010			

**ORDERING**

ITEM#	DESCRIPTION	TITLE 20	TITLE 24	CASE
91862	LED TONE-SELECT™ 9WA19/27-30-35-40-50K/DIMM/GU24	No	No	96

**ADDITIONAL INFORMATION:**

- Using the CCT slider on the side of lamp to select the desired color temperature.