



Item#: **92152 LED 6" TONE-SELECT™ RETROFIT CAN**INDOOR FIXTURE

FEATURES

- Adjustable color temperature for custom lighting application.
- Energy efficient: save up to 80% in energy costs
- · No flickering or noise.
- Instant-0n.

APPLICATION

Ideal for retrofitting inefficient fixtures in malls, hospitals, airports, offices, lobbies and other commercial applications.

ELECTRICAL

LIGHTING PERFORMANCE

Lumens	1000
Lumens Per Watt (LPW)	67
Color Temperature (CCT)	27K / 30K / 35K / 40K / 50K
Color Rendering (CRI)	90
R9 (Red Value)	
R13 (Skin Tones)	
Beam Angle	111°
Light Distribution	Type VS
BUG Rating (Backlight, Uplight, and Glare)	
Dimmable Lighting Control	Dimmable see compatibility report

ENVIRONMENT

Operating Temperature	-4° ~ 104°F
Suitable Location	WET Indoor / Covered Ceilings
Ingress Protection Rating	IP43

LIFESPAN

Average Life (Hours)	50,000
Warranty (Years)	5
COMPONENTS	

LED Light Source CONSTRUCTION

Housing	Aluminum / PC
Base / Power Supply	E26 - Medium
Finish	White

QUALIFICATIONS



Published lumens on LED products are approximate and may vary slightly. - Specifications are subject to change without notice.


Item#: **92152 LED 6" TONE-SELECT™ RETROFIT CAN**




				hes)

Length (MOL)	2.1"
Width/Diameter (MOD)	7.3"
Net Weight (Lbs)	

SUPPORTING DOCUMENTS (Grey = not available at this time.)				
Product Sheet	VIEW			
Install Instructions	VIEW			
Dimmer Compatibility	VIEW			
IES Download from Web Item	VIEW			
LM79	VIEW			





PACKAGING		UPC	DIMENSIONS (LxWxH)	GROSS WEIGHT (Lbs)
Master Carton	12	10811768023012		
Individual Box	1	811768023015	7.6" x 2.4" x 7.6"	
Country of Origin	China			
HS Tariff	8539.50.0010			

ORDERING

ITEM#	DESCRIPTION	TITLE 20	CASE
92152	LED 6IN TONE-SELECT™ RETROFIT CAN/15W/27-50K/DIMM/120V/MED		12
ACCESSORIES			
90905-QC	CONNECTOR FOR GU24 BASE ON 4" AND 5"/6" LED RETROFIT CAN		1

ADDITIONAL INFORMATION:

- Using the CCT slider on side of the retrofit can, select the desired color temperature prior to installation. See below:

VIEW

